Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For C146

Girder Clamp - HGC-S2-1T

1 Tonne Capacity
75-230mm Beam Width



New Release

Ex GST	Inc GST
$80.00	$92.00

ORDER CODE:	C146
MODEL:	HGC-S2-T1
Type:	Girder Clamp
Style:	Fixed - Manual
Load Capacity (Tonne):	1
Beam Width (mm):	75 - 230

Description

The 1-tonne Girder Clamp is a versatile, secure, and easy-to-use solution designed for attaching lifting equipment to structural steel beams. Engineered for reliability, this clamp provides a safe anchorage point for hoists, chain blocks, and lifting devices during material handling operations.

Manufactured from high-strength alloy steel, the clamp features a robust, adjustable jaw opening that allows it to fit a wide range of beam sizes. Its simple screw-thread locking mechanism ensures a firm and stable grip on the beam, preventing slippage while maintaining ease of installation and removal.

Ideal for workshops, warehouses, construction sites, and maintenance applications, the 1T Girder Clamp delivers a dependable lifting connection that complies with relevant safety standards. Whether used for fixed lifting points or temporary lifting setups, it offers both strength and convenience in a compact design.

Features

- Robust all steel construction
- Manually adjustable to various beam widths
- Provides a connection point for hoists
- Can be used in different locations as required
- Each girder clamp is supplied with an individual serial number, stamped on both the clamp body and the stainless-steel identification plate.
- Adjustable design to accommodate a wide range of beam and flange widths.
- Simple, quick mounting suitable for both permanent installations and temporary lifting applications.
- Special clamp jaw design applies load away from the edge of the flange, reducing flange stress.Built-in load bar provides reduced headroom
- Additional security is provided by threaded adjustment screws secured by using the countersunk allen head screw to lock the threaded adjustment bar in position with a copper flat.
- QR Code scan for quick manual specifications
- Rated Capacity 1 Tonne
- Beam Size range 75mm-230mm
- Complies to AS 4991

Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For C146


Specific Features



Top View



Left View



Low View



Front View 1



Front View 2



Front View 3

Recommended Accessories

C143
Chain Block



K090
Mobile Girder Rail Gantry Package Deal

