

Product Brochure For C3119

Air Compressor - Belt Drive - 16RSE-DC

50 Litre Tank / 2.7hp
15.7cfm / 445lpm Piston Displacement



New Release

Ex GST	Inc GST
\$2,566.00	\$2,950.90

ORDER CODE:	C3119
MODEL:	16RSE-DC
Drive Type:	Belt
Piston Displacement (CFM / LPM):	15.7 / 445
Free Air Delivery (CFM / LPM):	10.6 / 300
Cylinders (Type):	3
Max. Pressure (kPa):	931
Max. Pressure (PSI):	135
Air Receiver Tank Size (Litre):	50
Motor Speed (rpm):	970
Motor Power (kW / hp):	2.0 / 2.7
Voltage / Amperage (V / amp):	230 / 15
Nett Weight (kg):	81

MARQUIP



Description

16RSE-DC belt-drive heavy duty professional unit suitable for medium demand air tools and spray guns required to produce a professional automotive quality finish.

Dual capacitor start / run 2.7HP motor is complete with overload and manual reset, IP54 rating, TEFC (totally enclosed, fan cooled) and 15 Amp plug and overload.

Air receiver is painted to an automotive quality finish.

MARQUIP electric compressors have been assembled in New Zealand since 1946. The pump is fully cast iron with a low speed of 970rpm ensuring a long life. The compressor produces a displacement of at least 15.7cfm (445 litre/min) and free air delivery of 300 litre/min – arguably the biggest single phase compressor available. A reliable 230V / 15 Amp circuit must be available when operating this unit. Extension leads must be heavy duty.

The DUAL CONTROL or "DC" feature permits the compressor to be switched from pressure switch ONLY operation to continuous run when operating under a high duty cycle.

"DC" Dual Control version which features:

Automatic STOP/START pressure switch (PS) control and automatic free-running air governor (AG) control depending on compressor use and duty the best method of operating can be chosen to suit the job. Heavy duty cast iron pump has cast iron cylinders, air cooled by a large fan-type flywheel. German made pressure switch, Italian check valves, Vibration resistant liquid filled gauges. Efficient air intake filters reduce noise and low revving speed extends pump life

Pump: TA65

Dimensions (L x W x H): 110 x 40 x 80 cm

Features

- Receiver Certified to Australian/NZ Standards
- Heavy duty, high capacity pump (refer sku TA65 for parts)
- Dual control: pressure switch or continuous run
- Impact resistant galvanized safety guard
- Copper delivery pipe
- Performance data in accordance with CAAA protocol

Product Brochure For C3119

Recommended Accessories

H045

Retractable Air Hose Reel -
Includes Air Dusting gun



H040

Industrial Retractable Air Hose
Reel



H008

Industrial Polymer Air Hose



H018

Recoil PU Air Hose



A250

Hi Flow Air Duster Gun



A251

Hi Flow Air Duster Gun



S440

Air Blow Gun



A264

Professional Tyre Inflator with
Linear Gauge



Product Brochure For C3119

A043

Air Micro Die Grinder Kit



A046

Air Pop Rivet Kit



A040

Air Die Grinder



A041

Air Die Grinder - Extended Shaft 5" (127mm)



A082

Air Nibbler



F935

High-Flow Air Fittings



F941

High-Flow One Touch System Air Fittings



F945

High-Flow One Touch System Air Fittings



F951

High-Flow Air Fittings



F950

High-Flow Air Fittings




F955

High-Flow Air Fittings



F803

Air Fittings



Product Brochure For C3119

F811
Air Fittings



F930
Air Fittings

