Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For D4436

# 3MT x JT6 Drill Chuck Arbor - 1/2" BSW Threaded Shank

Suits Ø13mm Drill Chucks

| Ex GST | Inc GST |
|---|---|
| $44.00 | $50.60 |

| | |
|---|---|
| ORDER CODE: | D4436 |
| Long Taper (MT): | 3MT |
| Short Taper (JT): | JT6 |
| Suits Chuck Size (mm): | 13 |
| Threaded Shank: | 1/2" BSW |



## Description

Drill chuck arbors have one end which is the taper of the machine. The most common are Morse Tapers for mounting in a drill press spindle or lathe, or NT tapers for mounting in milling machines. The other end of the arbor is a short taper called a Jacobs Taper that is driven into the taper in the chuck body. The JT taper or Jacobs Taper is the most commonly used taper for mounting a drill chuck. The most common tapers used in Australia are JT2, JT3, JT4 & JT6

## Features

- Hardened & precision ground with 1/2" BSW drawbar thread

Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

# Product Brochure For D4436

## Recommended Accessories

C289
Heavy Duty Drill Chuck - Keyed Type



C299
Safety Lock Drill Chuck - Keyless Type



C292
Industrial Drill Chuck - Keyless Type

