

Product Brochure For G062

Air Operated - Grease Gun - P3 powerlube® P3-01C

Suits 20kg Drum

ORDER CODE:	G062
MODEL:	P3 powerlube® P3-01C
Type:	Air Operated & Grease Gun
Size:	20kg Drum

**Description**

The P3 POWERLUBE® P3-01C is the ultimate in high pressure, air-powered greasing. With models available to suit containers from 12.5kg (28 lbs.) to 20 kg (48 lbs.), it is fitted with a 50:1 ratio air motor which can run off most small compressors to provide fast, continuous greasing. The P3 POWERLUBE is also suitable for underground coal mine applications.

For Warranty Terms and Conditions - [click here](#)

Features

- Quiet, non-corroding air motor
- Grease viscosity: up to NLGI No.2
- Wetted components: zinc and hard chrome plated carbon steel, brass, and nitrile and polyurethane rubber
- Output: approx. 460 g/min (16 oz/min)
- Max. air pressure: 1,030 kPa (150 psi, 10.3 bar)
- Min. air pressure: 400 kPa (60 psi, 4 bar)
- Min. compressor size: 0.08 m³/min (3 cfm)
- Air inlet/fluid outlet: ¼" NPT (F)
- Pump ratio: 50:1 (grease pressure is 50 times air)
- B2 gun pressure: up to 69,000 kPa (10,000 psi, 690 bar) (boost pressure)
- Hose thread: ¼" NPT (M) TA-7K Filter & Regulator Kit
- Low air consumption
- No air line lubricator required
- Rubber edged follower plate
- 4m (13 ft.) x 6 mm (¼") ID delivery hose
- B2 booster gun with 360° ZSB swivel
- Fully serviceable
- 10 Year Macnaught Warranty

Optional Accessories

- TR5 Trolley
- PDF13 Push On Extension
- PDF21 Push On Extension
- TA-7K Filter & Regulator Kit
- KZDXL Straight Needlepoint Coupler
- KRV Pressure Release Valve

Product Brochure For G062

