

Product Brochure For K125

Bench Mount Thicknesser - Spiral Head Package Deal - T-13S

330 x 152mm (W x H) Material Capacity

Patented Spiral Cutter Head includes 26 x HSS inserts & 30 Tungsten Inserts



On Sale - Limited Stock

Ex GST

Inc GST

\$1,020.00

\$1,173.00

\$860.00

\$989.00

Package Contents - SAVE \$232.30 (Inc)

1 x W815 - Bench Mount Thicknesser - Spiral Head T-13S \$966.00
3 x W817 - Carbide Inserts for Spiral Cutter Heads on Thicknessers \$85.10

Normal Price (Inc): \$1,221.30

ORDER CODE:	K125
MODEL:	T-13S
Material Width Capacity (mm):	330
Material Height Capacity (mm):	152
Minimum Material Length (mm):	178
Maximum Depth of Cut (mm):	1.5mm @ 330mm Wide & 3.3mm @ 152mm Wide
Cutter Type:	HSS Inserts - Spiral
Quantity of Cutters (No. x Type):	26 x Inserts
Cutter Block Diameter (mm):	50.8
Cutter Block Speed (rpm):	10000
Quantity of Spirals (No.):	~
Length of Table (mm):	250
Length of Table with Extensions/Rollers (mm):	720
Feed Speed (m/min):	7
Dust Outlet Diameter (mm):	100/63
Motor Power (kW / hp):	1.8 / 2.4
Voltage / Amperage (V / amp):	240 / 10
Floor Space (W x D x H) (mm):	550 x 720 x 485
Floor Space With Option Stand (W x D x H) (mm):	570 x 720 x 1255
Nett Weight (kg):	30

Description

The T-13S sets itself apart from traditional thicknessers with its upgraded spiral cutter head, now standard on this model. Unlike conventional straight blade systems, the spiral design delivers a shearing action as it engages the workpiece. This results in a significantly smoother finish with reduced chipping and tear-out, along with noticeably quieter operation compared to the loud chopping action of traditional HSS cutter heads.

The cutter head is fitted with 26 replaceable HSS inserts that are easy to index or swap out using the included torque key. Since each insert sits at a fixed height, there's no need for time-consuming setup or adjustments—just unscrew and replace.

Thickness adjustment is made via a precision control lever located on top of the machine, working in tandem with a measurement scale on the front for quick reference. Additional features include a front-mounted depth of cut gauge and a lower-mounted preset depth stop with fixed positions at 1/8", 1/4", 3/8", and 1/2", allowing for consistent and repeatable results.

Built for reliability and performance, the T-13S combines a robust frame with thoughtful features to meet the demands of serious woodworkers and small production workshops.

Features

- Ideal portable machine
- 1.8kW / 2.4hp 240V motor
- 330mm x 152mm timber capacity
- Spiral cutter head includes 26 x HSS inserts
- Pre-set depth stop with 4 settings - 1/8", 1/4", 3/8", 1/2"
- Cut thickness indicator
- Power timber feed rollers
- Safety NVR switch
- 4 post design
- Anti-Kick back fingers

Product Brochure For K125

- Extension tables
- Includes 100/63mm dust chute
- A dust collector is required with this thicknesser

Includes

- 3 x Tungsten inserts - (10 Inserts Per Pack) (W817)

Recommended Accessories

W810

Universal Tool Stand



W618

Bench Planer Jointer



W817

Carbide Inserts for Spiral Cutter
Heads on Thicknesser



W886

Dust Collector



W394

Dust Collector



W930

Mobile Base



W931

Mobile Base - Heavy Duty



W332

Dust Collector



Product Brochure For K125

W344

Wood Dust Accessory Kit



W334

Dust Hose Reducer



W333

Dust Hose Reducer



W335

Blast Gate



W336

Dust Hose Elbow - 90 Degree



W337

Dust Hose Y Adaptor



W338

Dust Hose Universal Dust Hood



W339

Dust Hose Floor Sweeper Attachment



W3405

Dust Hose Clamp



W334A

Dust Hose Stepped Reducer



W340

Dust Hose Clamp



W343

Roller Stand



Product Brochure For K125

W343A
Roller Stand



W3434
Roller Stand

