

Product Brochure For L543D

Centre Lathe - AL-346

Ø330 x 600mm Turning Capacity - Ø40mm Spindle Bore
16 Geared Head Speeds 70 ~ 2000rpm, Includes Digital Readout System, Leadscrew Covers, Foot Brake & Cabinet Stand



Back In Stock Soon

Ex GST

Inc GST

\$8,162.00

\$9,386.30

ORDER CODE:	L543D
MODEL:	AL-346
Swing Over Bed (mm):	330
Distance Between Centres (mm):	600
Spindle Bore (mm):	40
Swing In Gap (mm):	~
Swing Over Cross-slide (mm):	200
Digital Readout System Fitted:	Yes
Quick Change Toolpost Fitted:	~
Leadscrew Covers Fitted:	Yes
Taper Turning Attachment:	~
Coolant System:	Yes
Tool Height To Suit (mm):	12
Centre Height (mm):	165
Spindle Nose Size or Type:	D1-4 Camlock
Bed Width (mm):	181
Headstock Spindle Taper (MT):	5
Tailstock Taper (MT):	3
Cross Slide Travel (mm):	160
Compound Slide Travel (mm):	85
Leadscrew Type:	Metric
Metric Cross Feed (X-Axis) (mm/rev):	0.013-0.31
Imperial Cross Feed (X-Axis) (inch/rev):	~
Metric Longitudinal Feed (Z-Axis) (mm/rev):	0.013-0.31
Imperial Longitudinal Feed (Z-Axis) (inch/rev):	~
Metric Thread Steps & Pitch (No. / mm):	32 (0.4 - 7)
Imperial Thread Steps & TPI (No. / TPI):	36 (4 - 60)
3 Jaw Chuck Diameter (mm):	160
4 Jaw Chuck Diameter (mm):	200
Spindle Steps / Speeds (No. / rpm):	16 (70 - 2000)
Motor Power (kW / hp):	1.8 / 2.4
Voltage / Amperage (V / amp):	415 / 10
Nett Weight (kg):	560

Features

- 2 Axis digital readout
- Gear drive headstock for quick change of spindle speeds
- Precision 'V'-beds are hardened and ground, incorporating a rigid webbed casting
- Concertina leadscrew cover
- Slide out swarf tray from front of machine
- Low voltage work light
- Foot operated spindle brake with safety cut out switch
- Slide out front swarf tray for easy cleaning
- Change gears for metric and imperial thread cutting
- Oil sight glass for head stock and gearbox
- Adjustable taper roller bearings support the spindle
- 16 spindle speeds from 70 to 2000rpm
- Inching button is incorporated on the control panel for convenient spindle speed selection
- Enclosed quick action gearbox for thread cutting and auto feeding
- Powered longitudinal and cross feeds
- D1-4 camlock spindle for quick chuck changes and safe reverse direction turning. ISO standard
- Dual calibrated dials (except for saddle hand-wheel)
- Chuck & change gear guards are fitted with micro switches

Product Brochure For L543D

Includes

- 2 Axis digital readout system
- Concertina leadscrew cover
- Slide out front swarf tray
- 3-jaw chuck with reverse jaws
- 4-jaw chuck
- Face plate
- Fixed steady
- Travelling steady
- Coolant system
- Change gears
- Dead centres
- Thread-chasing dial
- Safety chuck guard
- Work light
- Stand
- Foot brake
- Rear splash guard & slide out swarf tray
- Tool box
- Instruction booklet

Specific Features



2 Axis Digital Readout



Headstock



Spindle Speeds

Position	B5	B4	C4	C3	C2	A4	D2	E4	A2	E2
1	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
2	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
3	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
4	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
5	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
6	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
7	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
8	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
9	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
10	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
11	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
12	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
13	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
14	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
15	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
16	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
17	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
18	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
19	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
20	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
21	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
22	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
23	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
24	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
25	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
26	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
27	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
28	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
29	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
30	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
31	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
32	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
33	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
34	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
35	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
36	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
37	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
38	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
39	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
40	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
41	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
42	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
43	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
44	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
45	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
46	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
47	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
48	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
49	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
50	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
51	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
52	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
53	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
54	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
55	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
56	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
57	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
58	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
59	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
60	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
61	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
62	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
63	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
64	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
65	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
66	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
67	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
68	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
69	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
70	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
71	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
72	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
73	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
74	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
75	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
76	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
77	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
78	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
79	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
80	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
81	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
82	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
83	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
84	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
85	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
86	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
87	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
88	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
89	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
90	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
91	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
92	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
93	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
94	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
95	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
96	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
97	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
98	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
99	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8
100	0.1	0.125	0.16	0.2	0.25	0.32	0.4	0.5	0.63	0.8


Thread Charts 1

mm	0.5	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.0	2.2	2.5	2.8	3.2	3.6	4.0	4.5	5.0	5.6	6.3	7.0
----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----


Product Brochure For L543D




Leadscrew Covers




Saddle Left View



Saddle Controls



Saddle Right View



Compound Slide



Compound Slide Angle Scale




Thread Chasing Dial




Forward Reverse Spindle Lever



Tailstock




Tailstock Adjustments



Tailstock Graduations



Induction Hardened Bedways



Feed and Threading Engagement Levers



Cross Feed Dial Graduations




Saddle Hand Wheel Graduations



Compound Slide Dial Graduations

Product Brochure For L543D



Pull out Swarf Tray



Footbrake



Parts



Left View



Rear View

Recommended Accessories

M002
Steel Machine Mount & Rubber Insert

L292
Quick Change Toolpost

L295
Quick Change Toolpost

L277
Vertical Mill Slide



Product Brochure For L543D

C980
5C Collet Lathe Adaptor



L015
Right Hand Turning Tool Holder



L016
Left Hand Turning Tool Holder



L0099
Lathe Turning Tool Kit - 7 piece Insert Type



L450
Lathe Turning Tool Kit - 3 piece Insert Type



L456
Lathe Threading Tool Kit - Insert Type



L464
Professional Lathe Parting Tool Kit - Insert Type



L073
Parting Tool Holder - Suits 1/2" HSS Tool Bit



L076
Knurling Tool Holder Kit



C052
3MT Live Centre



C045
3MT Pipe Centre - 70° Cone



C290
Heavy Duty Drill Chuck - Keyed Type



Product Brochure For L543D

D443A
3MT x JT3 Drill Chuck Arbor



D1272
Metric 135° Precision HSS Drill Set - 25 Piece



D1282
Imperial 135° Precision HSS Drill Set - 29 Piece



D126
Metric 135° Precision HSS Drill Set - 170 Pieces



S090A
Soluble Metal Cutting Fluid - 1 Litre



S090
Soluble Metal Cutting Fluid - 5 Litre



S076
Cutting Tool Lubricant Fluid - 500ml



S077
Drilling, Tapping & Cutting Tool Lubricant Spray - 400g



S074
Cutting Tool Lubricant Paste - 500g




G660
Lathe Leadscrew Cover Kit



G659
Lathe Leadscrew Cover Kit - Concertina




L3455
Professional Sheet Metal Fabrication Book



Product Brochure For L543D

L341
Fitting and Machining Technical Book



L345
Handy Workshop Tips & Techniques - 1st Edition



L300
Magnetic Swarf Remover




M9991
Magnetic Floor Sweeper



M800
Rubber Mat - Anti-Fatigue



M805
Rubber Mat - Anti-Fatigue



O043
Rust & Corrosion Preventive



O042
General Purpose Lubricant & Corrosion Inhibitor



O044
Rust & Corrosion Preventive

