

Product Brochure For L606D

Centre Lathe - CL-460

Ø460 x 1000mm Turning Capacity - Ø80mm Spindle Bore
Includes Digital Readout System, Quick Change Toolpost, Taper Turning Attachment & Auto Slide-way Lubrication



Ex GST **Inc GST**
\$21,656.00 **\$24,904.40**

| | |
|---|----------------|
| ORDER CODE: | L606D |
| MODEL: | CL-460 |
| Swing Over Bed (mm): | 460 |
| Distance Between Centres (mm): | 1000 |
| Spindle Bore (mm): | 80 |
| Swing In Gap (mm): | 690 |
| Swing Over Cross-slide (mm): | 274 |
| Digital Readout System Fitted: | Yes |
| Quick Change Toolpost Fitted: | Yes |
| Leadscrew Covers Fitted: | Yes |
| Taper Turning Attachment: | Yes |
| Coolant System: | Yes |
| Tool Height To Suit (mm): | 25 |
| Centre Height (mm): | 230 |
| Spindle Nose Size or Type: | D1-8 Camlock |
| Bed Width (mm): | 300 |
| Headstock Spindle Taper (MT): | 6 |
| Tailstock Taper (MT): | 4 |
| Cross Slide Travel (mm): | 285 |
| Compound Slide Travel (mm): | 128 |
| Leadscrew Type: | Metric |
| Metric Cross Feed (X-Axis) (mm/rev): | 0.014 - 0.784 |
| Imperial Cross Feed (X-Axis) (inch/rev): | ~ |
| Metric Longitudinal Feed (Z-Axis) (mm/rev): | 0.031 - 1.70 |
| Imperial Longitudinal Feed (Z-Axis) (inch/rev): | ~ |
| Metric Thread Steps & Pitch (No. / mm): | 47 (0.1 - 14) |
| Imperial Thread Steps & TPI (No. / TPI): | 60 (2 - 112) |
| 3 Jaw Chuck Diameter (mm): | 250 |
| 4 Jaw Chuck Diameter (mm): | 350 |
| Spindle Steps / Speeds (No. / rpm): | 12 (25 - 1860) |
| Motor Power (kW / hp): | 5.5 / 7.5 |
| Voltage / Amperage (V / amp): | 415 |
| Nett Weight (kg): | 1950 |

Features

- 2 axis digital readout system
- Quick change toolpost
- Taper turning attachment fitted to saddle
- Automatic lubrication pump oiling slides
- Triple bearings supporting headstock spindle
- Adjustable taper roller bearings providing spindle accuracy
- Precision 'V'-beds & headstock gears are all hardened & ground
- One piece cast iron base increases rigidity
- Overload protection on drive motor and coolant system
- Universal enclosed gearbox incorporating metric & imperial thread capabilities
- Inching button incorporated on the control panel for convenient spindle speed selection
- Foot operated spindle brake with safety cut out switch
- 300mm wide induction hardened heavy duty cast iron bed
- Removable gap bed allowing workpiece to swing up to 690mm
- Chuck guard fitted with safety micro switch
- Powered longitudinal and cross feeds
- Adjustable 5 position length-stop mechanism for accurate repetitive operation
- Micro adjustable saddle stop
- Dual calibrated cross feed dial incorporating metric & imperial graduations
- Coolant system with flexible hose enabling operator to manipulate flow direction
- Oil level sight glass for headstock and gearbox

Product Brochure For L606D

- Low voltage halogen work light
- D1-8 camlock spindle for quick chuck removal
- 12 spindle speeds from 25-1860rpm
- Large 80mm spindle bore
- 5.5kW / 7.5HP 415V main motor

Includes

- 2 axis digital readout system
- Taper turning attachment
- Quick change toolpost
- Auto lubrication pump for slides
- Concertina leadscrew covers
- 250mm 3-jaw chuck with reverse jaws
- 350mm 4-jaw chuck
- 350m face plate
- Fixed steady with roller bearings
- Travelling steady with brass guides
- Dead centres
- Thread chasing dial
- Foot brake
- Coolant system
- LED Work light
- Rear splash guard
- Spindle reducing bush

Specific Features



2 Axis Digital Readout




Safety Chuck Guard



Headstock Controls



Speed Selection Levers and Feed Levers




Feed Chart



Feed Lever



Automatic Lubrication System




Removable Gap Bedway

Product Brochure For L606D




Hardened and Ground Bed



Taper Turning Attachment




Taper Turning Attachment Close Up



Taper Turning Attachment Full View



Saddle Front View



Quick Change Toolpost



Saddle Safety Guard




Saddle Safety Guard Shown Open



Leadscrew Covers



Thread Chasing Dial



Spindle Engagement Lever



Saddle Right View




Compound Slide



Compound Angle Scale



Saddle Controls



5 Position Adjustable Length Stop


Product Brochure For L606D



Cross Feed Dial in Metric Mode



Cross Feed Dial in Imperial Mode



Compound Slide Dial in Metric



Saddle Dial In Metric



LED Worklight and Coolant Hose



LED Worklight Close Up



Fixed Steady with Roller Guides



Travelling Steady with Roller Guides



Tailstock



Tailstock Quill Graduations



Tailstock with Horizontal Adjustment



Tailstock Dial in Metric



Footbrake



80mm Spindle Bore

Product Brochure For L606D

Recommended Accessories

L048
Right Hand Turning Tool Holder



L049
Left Hand Turning Tool Holder



L041
Right Hand Turning Tool Holder



L042
Left Hand Turning Tool Holder



L453
Lathe Turning Tool Kit - 3 piece
Insert Type



L459
Lathe Threading Tool Kit - Insert
Type



L467
Professional Lathe Parting Tool
Kit - Insert Type



L294A
Quick Change Toolpost Holder -
Std



Product Brochure For L606D

C046
4MT Pipe Centre - 70° Cone



C290
Heavy Duty Drill Chuck - Keyed Type



C294
Industrial Drill Chuck - Keyless Type



D454A
4MT x JT3 Drill Chuck Arbor



D424
Drill Sleeve - Morse Taper



D422
Drill Sleeve - Morse Taper



D1272
Metric 135° Precision HSS Drill Set - 25 Piece



D1282
Imperial 135° Precision HSS Drill Set - 29 Piece



D126
Metric 135° Precision HSS Drill Set - 170 Pieces



D119
Metric 2MT HSS Drill Set



S090A
Soluble Metal Cutting Fluid - 1 Litre



S090
Soluble Metal Cutting Fluid - 5 Litre



Product Brochure For L606D

S076

Cutting Tool Lubricant Fluid - 500ml



S077

Drilling, Tapping & Cutting Tool Lubricant Spray - 400g



S074

Cutting Tool Lubricant Paste - 500g



S091

Soluble Metal Cutting Fluid - 20 Litre



G660

Lathe Leadscrew Cover Kit



A358

Sky Hook Lifting Device



A358A

Chuck Hook



L300

Magnetic Swarf Remover



M9991

Magnetic Floor Sweeper




M800

Rubber Mat - Anti-Fatigue



M805

Rubber Mat - Anti-Fatigue



O043

Rust & Corrosion Preventive



Product Brochure For L606D

O042

General Purpose Lubricant &
Corrosion Inhibitor



O044

Rust & Corrosion Preventive

