

## Product Brochure For L681

### Centre Lathe - AL-335F

300 x 910mm Turning Capacity

Includes Foot Brake, Coolant Pump System & Cabinet Stand



ORDER CODE:	L681
MODEL:	AL-335F
Swing Over Bed (mm):	300
Distance Between Centres (mm):	910
Spindle Bore (mm):	38
Swing In Gap (mm):	450
Swing Over Cross-slide (mm):	178
Digital Readout System Fitted:	Optional
Quick Change Toolpost Fitted:	Optional
Leadscrew Covers Fitted:	~
Taper Turning Attachment:	~
Coolant System:	Yes
Tool Height To Suit (mm):	12
Centre Height (mm):	150
Spindle Nose Size or Type:	D1-4 Camlock
Bed Width (mm):	180
Headstock Spindle Taper (MT):	5
Tailstock Taper (MT):	3
Cross Slide Travel (mm):	170
Compound Slide Travel (mm):	85
Leadscrew Type:	Imperial
Metric Cross Feed (X-Axis) (mm/rev):	~
Imperial Cross Feed (X-Axis) (inch/rev):	0.02 - 0.33
Metric Longitudinal Feed (Z-Axis) (mm/rev):	~
Imperial Longitudinal Feed (Z-Axis) (inch/rev):	0.07 - 1.29
Metric Thread Steps & Pitch (No. / mm):	36 (0.4 - 7)
Imperial Thread Steps & TPI (No. / TPI):	45 (4 - 60)
3 Jaw Chuck Diameter (mm):	160
4 Jaw Chuck Diameter (mm):	200
Spindle Steps / Speeds (No. / rpm):	9 (75 - 1400)
Motor Power (kW / hp):	1.5 / 2
Voltage / Amperage (V / amp):	240 / 10
Nett Weight (kg):	500

### Description

This new & improved AL-335F quality metal turning lathe and now includes a coolant system & foot brake for the serious enthusiastic home model engineer, general maintenance and small workshops. Featuring a precision ground, induction hardened bed, fully gear driven spindle with hardened and ground gears with a speed range of 75 - 1400rpm, selectable via the front of headstock mounted gear selection levers.

2hp single phase 240 volt motor is supplied on machine, taper roller spindle bearings, range of cross and longitudinal feed speeds selected on a separate gearbox, thread chasing dial, chuck guard with safety interlock, splash guard and work lamp.

Supplied with a large range of standard accessories including a 150mm(6") 3 jaw self centring chuck, 200mm(8") 4 jaw independent chuck, face plate and dead centres. 5 to 3 MT reduction sleeve, steady rest, follow rest, standard tool post, floor stand with a swarf tray. Change gears and toolbox with maintenance tools.

### Features

- Gear driven headstock for quick change of spindle speeds
- Foot operated spindle brake with safety cut out switch
- Slide out front swarf tray for easy cleaning
- Coolant pump system with flexible hose & nozzle
- Precision V-beds are induction hardened and ground, incorporated with rigid webbed castings
- Low voltage halogen work light
- Change gears for metric and imperial thread cutting
- Adjustable taper roller bearings support the spindle
- 9 spindle speeds from 75 to 1400rpm

## Product Brochure For L681

- Saddle hand wheel mounted on right side of apron reducing swarf contacting the hand
- Inching button is incorporated on the control panel for convenient spindle speed selection
- Quick-action gearbox for thread cutting and auto feeding
- D1-4 camlock spindle for quick and accurate chuck removal and safe reverse direction turning. ISO standard
- External adjustable cross feed lead-screw nut
- Powered longitudinal and cross feeds
- Bed wipers on saddle
- Removable gap bed-way for larger diameter jobs
- Dual calibrated dials (except for saddle hand-wheel)
- Chuck guard fitted with safety micro switch
- Chuck & change gear guards are fitted with micro switches

### Includes

- Foot brake system
- Coolant pump system
- Slide out front swarf tray
- Work light with flexible arm
- 3-jaw chuck with reverse jaws
- 4-jaw chuck
- Face plate
- Fixed steady
- Travelling steady
- Change gears
- Dead centre
- Thread-chasing dial
- Rear splash guard & swarf tray
- Safety chuck guard
- Cabinet stand
- Spanners
- Tool box
- Instruction booklet

### Specific Features



Front View



Left View



Headstock




Spindle Speed Levers




Control Panel Switches



Feed and Thread Gearbox



Spindle Speed Chart



Metric Feed Chart

Product Brochure For L681

position	E2	E3	E4	B2	B3	C3	C4	A1
SII	0.083	0.071	0.064	0.059	0.053	0.047	0.046	0.041
SI	0.161	0.138	0.125	0.115	0.104	0.092	0.089	0.079
	0.041	0.035	0.032	0.030	0.027	0.024	0.023	0.020

position	D4	C4	C3	C2	A4	B2	E4	A2	E2
MI	1.4	1.6	1.5	1.565	1.3	1.25	1.7	1.75	1.675
MII	1.8	1.8	1	1.195	1.2	1.25	1.4	1.5	1.75
MI	1.8	1.8	2	2.25	2.4	2.5	2.8	3	3.5
MII	3.2	3.6	4	4.5	4.8	5	5.6	6	7

Imperial Feed Chart

position	D4	C4	C3	C2	A4	B2	E4	A2	E2
MI	1.4	1.6	1.5	1.565	1.3	1.25	1.7	1.75	1.675
MII	1.8	1.8	1	1.195	1.2	1.25	1.4	1.5	1.75
MI	1.8	1.8	2	2.25	2.4	2.5	2.8	3	3.5
MII	3.2	3.6	4	4.5	4.8	5	5.6	6	7

position	A2	A3	C3	A4	C3	C3	A1	D4
Z	24	24	38	24	22	24	26	24
MI	4	4 1/2	5 1/2	5	3 1/2	6	6 1/2	7 1/2
MI	8	9	19	10	11	12	13	14
Z	48	48	38	48	44	48	52	48
MII	16	18	19	20	22	24	26	30
MI	32	36	38	40	44	48	52	60

Metric and Imperial Thread Charts

1/16"	SCALE	1/16"	SCALE
4	1-8	13	1*5
4 1/2	1	14	1*3*5*7
5	1*5	15	1*5
6	1*3*5*7	16	
7	1*5	18	1*3*5*7
8		19	1*5
9	1*5	20	1-8
10	1*3*5*7	22	1*3*5*7
11	1*5	24	
12	1-8	28	1*3*5*7

Indicator Table




Chuck Guard




3 Point Steady



Saddle



Saddle Left View



Feed Engagement Lever



Toolpost



2 Point Steady



Halogen Light and Coolant System



Thread Chasing Dial



Compound Slide Hand Wheel



Cross Feed Handle



Saddle Hand Wheel



Compound Slide


Product Brochure For L681




Forward Reverse Spindle Lever




Tailstock



Tailstock Quill



Tailstock Handle



Induction Hardened Bedways




Safety Footbrake



Slide Out Swarf Tray



Side Access Door to Change Gears



Safety Micro Switch on Side Access Door

Product Brochure For L681

**Recommended Accessories**

**D695**  
3-Axis Optimum Digital Readout Counter - 1µm



**D694**  
1500mm Optimum Magnetic Digital Readout Scale



**D720C**  
200mm Easson Digital Readout Scale



**D728**  
600mm Easson Digital Readout Scale



**P235**  
Coolant Pump & Tank



**L292**  
Quick Change Toolpost



**L295**  
Quick Change Toolpost



**L277**  
Vertical Mill Slide



Product Brochure For L681

**C980**  
5C Collet Lathe Adaptor



**L015**  
Right Hand Turning Tool Holder



**L016**  
Left Hand Turning Tool Holder



**L0099**  
Lathe Turning Tool Kit - 7 piece  
Insert Type



**L450**  
Lathe Turning Tool Kit - 3 piece  
Insert Type



**L456**  
Lathe Threading Tool Kit - Insert  
Type



**L464**  
Professional Lathe Parting Tool  
Kit - Insert Type



**L073**  
Parting Tool Holder - Suits 1/2"  
HSS Tool Bit



**L076**  
Knurling Tool Holder Kit



**C052**  
3MT Live Centre



**C045**  
3MT Pipe Centre - 70° Cone



**C290**  
Heavy Duty Drill Chuck - Keyed  
Type



Product Brochure For L681

**D443A**  
3MT x JT3 Drill Chuck Arbor



**D1272**  
Metric 135° Precision HSS Drill Set - 25 Piece



**D1282**  
Imperial 135° Precision HSS Drill Set - 29 Piece



**D126**  
Metric 135° Precision HSS Drill Set - 170 Pieces



**S090A**  
Soluble Metal Cutting Fluid - 1 Litre



**S090**  
Soluble Metal Cutting Fluid - 5 Litre




**S076**  
Cutting Tool Lubricant Fluid - 500ml



**S077**  
Drilling, Tapping & Cutting Tool Lubricant Spray - 400g



**S074**  
Cutting Tool Lubricant Paste - 500g




**G660**  
Lathe Leadscrew Cover Kit



**G659**  
Lathe Leadscrew Cover Kit - Concertina




**L3455**  
Professional Sheet Metal Fabrication Book




Product Brochure For L681

L341  
Fitting and Machining Technical Book



L345  
Handy Workshop Tips & Techniques - 1st Edition



L300  
Magnetic Swarf Remover




M9991  
Magnetic Floor Sweeper



M800  
Rubber Mat - Anti-Fatigue



M805  
Rubber Mat - Anti-Fatigue



O043  
Rust & Corrosion Preventive



O042  
General Purpose Lubricant & Corrosion Inhibitor



O044  
Rust & Corrosion Preventive

