Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For M0022

Line Light R Rechargeable LED handheld Work Light - 03.5244XX

Inspection Hand Lamp with Top Spot Light
Up To 400 Lumen



ORDER CODE:	M0022
MODEL:	03.5244XX
Type:	LED Hand Work Light, with & Top Spot Light
Size (mm):	~
Light - Watts / Lumens / Kelvins (W / L / K):	5.5 / 400
Power (W):	~
Voltage / Amperage (V / amp):	5 / ~
Built-in Transformer (Yes / No):	~
Magnetic Base (Yes / No):	~
Charging Cable Type (metre):	~
Colour Temperature (K):	~
Nett Weight (kg):	0.450

Description

LINE LIGHT R - Rechargeable inspection hand lamp with top spot light

The LINE LIGHT R is an extremely powerful inspection light and flashlight in one.

The sturdiness of the LINE LIGHT R make it endure even strong strokes and shocks from daily use in the rough workshop environment. With its slim design (Ø25mm), it is possible to illuminate even the most narrow and hard to reach areas.

By means of a built-in prism, LINE LIGHT R concentrates the light in a 75° beam angle providing an extremely bright and powerful illumination of the specific working area. Avoid blinding during work and adjust the beam angle to provide optimal work light at the specific work area.

A flexible gooseneck with a strong built-in magnet or with suction cup fixture are available as optimal accessories.

LINE LIGHT R is made in Denmark

SEVEN BENEFITS BY LINE LIGHT R:
Improved light output increased by more than 170%
Powerful inspection light and flashlight in one
Rechargeable with up to 4h operating time
Sturdy and waterproof, IP65
New magnetic, electronic switch
Ultra-slim design (ø25mm) allows inspection in even the most inaccessible places

Features

- Details
- Product types Hand Lamp
- Net Weight 0.45kg
- Length 357mm
- Width 25mm
- Height 25mm
- In the box Lamp, Charge cable, Clip with hook & magnet & Manual

- Secondary Light
- Luminous Flux, Max 150 Lumen
  Illuminance, Max 1500 Lux

Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For M0022

- Beam Angle 50°
- CRI Ra>80
- CCT 6000
- Light Source Secondary 1 x CREE XP-G2
- Illuminance Distance 0.50 metre

- Main Light
- Light Source 16 SMD LED's
- Luminous Flux, Max 400 Lumen
- Illuminance, Max 900 Lux
- Illuminance Distance 0.50 Metre
- CRI Ra>80
- CCT 6000 Kelvin
- Beam Angle Main 75°

- Electrical
- Power source Rechargeable Battery
- Battery type Li-ion
- Battery capacity 2600mAh
- Battery voltage 3.70V
- Cable 1 m USB to mini DC
- Charging voltage DC 5V
- Charging current 1.00A
- Charging input voltage 100-240V AC 50/60Hz
- Max Power Consumption 5.5W

- Operation
- Operating time, up to 1.50 hours
- Charging time 6 hours
- Ingress protection IP65
- Impact protection IK07
- Operating temperature -10 °C to +40 °C

Specific Features


Rear View


Line Light R Hand Light


Rear View


Line Light R Hand Light


Shown with Magnetic Hook


Connecting The USB Charging Cable


Hand Held LED Light


Top LED Tube Light

Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For M0022



Rotating Switch to Activate Light Bar & Spot Light



Clip On Swivel Hook & Magnetic Back




Clip On Hook & Magnetic Back



Shown Clipped On To Light



Shown With Accessories



Shown In Use Automotive Industry



Shown In Use Automotive Industry