Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For P130M

Trade Hydraulic & Pneumatic Press - 30 Tonne - HPM-30

Robotic Welded Steel Frame Construction
Includes Adjustable Sliding Cylinder Ram, Pressure Gauge & Bending Vee Blocks

Ex GST	Inc GST
$1,404.00	$1,614.60



ORDER CODE:	P130M
MODEL:	HPM-30
Pressing Capacity (Tonne):	30
Hydraulic Ram Operation (Type):	Manual Hand Lever / & Pneumatic System
Sliding Ram (left-right) (Yes / No):	Yes
Width Between Front Posts (mm):	535
Width Between Side Posts (mm):	138
Table Top Opening - (Front to Back) (mm):	160
Ram To Table (Max.) (mm):	1035
Cylinder Stroke (mm):	155
Ram Diameter (mm):	Ø70
Piston Diameter (mm):	Ø80
Minimum Air Flow Rate required (L/Min):	200
Motor Power (kW / hp):	~
Voltage (V):	~
Floor Space (W x D x H) (mm):	950 x 700 x 1800
Nett Weight (kg):	200

METALMASTER

1 YEAR WARRANTY

Description

The Metalmaster HPM-30 30 tonne trade press has a variety of uses, ideal for removing and installing bushes, ball joints, bearings, gears, pulleys etc. The HPM-30 is pneumatically or hand operated for easy use and also has the added feature of a sliding head which can be moved to the side allowing for those offset pressing jobs.

This 30 tonne press has a fully robotic welded frame for the highest quality, accuracy and extra rigidity. The press is supplied with a pressure gauge, two heavy duty pressing plates, and can be fitted with an optional pneumatic foot pedal, making it ideal for mechanics, farmers or the serious home workshop.

Features

- Ideal for removing and installing - Bushing, Ball-joints, Bearings, Gears, Pulleys, etc
- Pneumatic or hand operation
- Heavy duty steel construction with robotic fully welded frame
- Hydraulics assembled in a temperature controlled clean room for maximum quality
- Hydraulics individually factory tested prior to shipping.
- Adjustable sliding head up to 200mm travel between the vertical post
- Metric / imperial pressure gauge included
- NOTE: Minimum Air Flow Rate required is 200 liters/minute

Includes

- Complete with vee blocks

Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For P130M

Specific Features


Robotic Welded Frame


Hydraulic Pnematic Hand Pump



Metric / Imperial Pressure Gauge


Table Pins With Safety Clips


Dual Purpose Pressing Blocks


Pneumatic Valve Control



Horizontal Sliding Ram


Ram Top View With Bearing Slide


Sliding Ram With Handle


Includes Removable Ram Top Cap



Front View




Left View


Rear View


Right Side View


left Side View


Dimensions

Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For P130M

Recommended Accessories

P1404
Hydraulic Press Guard



P1400
Pneumatic Foot Control




P030
Bush Driver Set - 17 piece



P031
Bearing Race & Seal Driver Set - 10 piece



P1401
Steel Press Pin Driver Set - 11 piece



P450
Pressbrake Attachment - Suits Hydraulic Presses

