

## Product Brochure For P174A

# Hydraulic Punch & Shear - 60 Tonne - IW-60SD

Dual Hydraulic Cylinders with Independent Operating Stations & Deep Throat Punching Station  
Three Punching Stations, Laser Punch Guide & 6 Sets of Round Punches & Dies

## Please Call



|  |   |
|--|---|
| ORDER CODE:                                | P174A                                   |
| MODEL:                                     | IW-60SD                                 |
| Punching Pressure (Tonne):                 | 60                                      |
| Punching Table Type:                       | Manual with Guides and Adjustable Stops |
| Punching (Diameter x Thickness) - MS (mm): | Ø22 x 20, Ø50 x 9                       |
| Punching Throat Depth (mm):                | 510                                     |
| Punching Maximum Stroke Length (mm):       | 100                                     |
| Punching Cycles (15mm Stroke) - MS (cpm):  | 30                                      |
| Punching Work Table Height (mm):           | 1010                                    |
| Flat Bar Shear (W x Thickness) - MS (mm):  | 350 x 15, 240 x 20                      |
| Flat Bar Shear - Blade Length - MS (mm):   | 360                                     |
| Flat Bar Shear Work Table Height (mm):     | 910                                     |
| Angle Shear 90° - MS (mm):                 | 130 x 130 x 13                          |
| Angle Shear 45° - MS (mm):                 | 65 x 65 x 8                             |
| Angle Flange Trim (mm):                    | 100                                     |
| Angle Shear Work Table Height (mm):        | 1115                                    |
| Round Solid Bar Shear - MS (mm):           | Ø40                                     |
| Square Solid Bar Shear - MS (mm):          | 38 x 38                                 |
| Solid Bar Shear Work Table Height (mm):    | 1220                                    |
| Notching - Rectangle - MS (mm):            | 50.8 x 90 x 9                           |
| Notching Work Table Height (mm):           | 910                                     |
| Multi Vee Die Block (mm):                  | ~                                       |
| Vee Opening Sizes (mm):                    | ~                                       |
| Max. Tonne Capacity (T):                   | ~                                       |
| Bending Work Table Height (mm):            | ~                                       |
| Motor Power (kW / hp):                     | 5.5 / 7.5                               |
| Voltage / Amperage (V / amp):              | 415                                     |
| Nett Weight (kg):                          | 2380                                    |

## Description

The Sunrise Punch & Shears are manufactured in Taiwan, also known as Ironworkers are well recognised in our Australian market for the machines being reliable & durable due to their structurally well manufactured unique design & engineering excellence. Sunrise is ISO-9001 certified by BVQI, and our products meet the CE safety requirements and regulations. Sunrise relentlessly seeks continuous improvement and product development to keep a step ahead of their competitors.

The double cylinder "S/SD" series have two control foot pedals, & separate operations can be safely performed simultaneously without interference. The low pressure setting for tool change provides maximum operation safety. The long punching cylinder stroke & deep throat enable mounting a wide range of special optional equipment. The large punching base with the "T-slot" fixing provide a solid base for securing the punching tooling, as well as a wide range of optional & custom designed tooling.

The hydraulic system & components that drives the shearing beam & punching head is considerably very quiet compared to most other machines and operates efficiently smooth in all modes. The electrical components & DC control circuit are operated at a low 24 volt system & provides full protection & safety with in the separate key locked cabinet.

The Sunrise machines have proven themselves over & over again to provide trouble free service for many years in production and we have references all around Australia to verify our statement.

## Features

- Laser punch guide system for easy alignment
- Five work stations, Punching, Notching, Plate Shearing, Angle Iron Shearing and Bar Shearing (all stations are guarded)
- Dual hydraulic cylinders allows simultaneous operation without interference
- Punching capacity up to 50mm standard
- Mitre cutting of angle iron



Product Brochure For P174A



Angle Shear



Angle Shear



Round Bar Shear



Square Bar Shear



Notcher



Work Light




Monoblock Design For Rigid Frame Structure



Keyed Punch Ram For Shaped Tool Alignment



Solid Punching Base With T-Slot Grooves




Optional Single Vee Pressbrake Attachment



Optional Multi Vee Pressbrake



Optional Vee Notcher Punch Side



Optional Channel Shear



Optional Hydraulic Holddown for Flat Shear



Optional Pipe Notcher




Optional Channel Punching Die Holder

Product Brochure For P174A



Optional Goose Neck Die Holder




Optional Large Hole Punching



Optional Angle Bending Press



Optional Multi Stop Gauge



Optional Duplicating Table

**Recommended Accessories**

P186

Single-Vee Pressbrake Bending Attachment



P189

Multi-Vee Pressbrake Bending Attachment



P165

Ø6-26mm Round Punch & Dies Set



P166

Ø11-40mm Round Punch & Dies Set

Product Brochure For P174A

**P726**  
Ø26mm Round Punch - RPN1



**P726A**  
Ø26.7mm Round Die - RDN1



**P6005**  
8 x 20mm Slotted Punch



**P6006**  
8.7 x 20.7mm Slotted Die



**P6001**  
8 x 8mm Square Punch




**P6002**  
8.7 x 8.7mm Square Die



**M800**  
Rubber Mat - Anti-Fatigue



**M805**  
Rubber Mat - Anti-Fatigue



**O043**  
Rust & Corrosion Preventive



**O042**  
General Purpose Lubricant & Corrosion Inhibitor



**O044**  
Rust & Corrosion Preventive

