

## Product Brochure For P175C

# IWNC-80SD - Hydraulic Punch & Shear with NC Table - 80 Tonne

Dual Hydraulic Cylinders with Independent Operating Stations  
Includes NC Programmable Positioning Table 1000 x 400mm

## Please Call



ORDER CODE:	P175C
MODEL:	IWNC-80SD
Punching Pressure (Tonne):	80
Punching Table Type:	NC Positioning & 1000 x 400mm (X & Y-Axis)
Punching (Diameter x Thickness) - MS (mm):	Ø26 x 22, Ø50 x 12
Punching Throat Depth (mm):	510
Punching Maximum Stroke Length (mm):	100
Punching Cycles (15mm Stroke) - MS (cpm):	29
Punching Work Table Height (mm):	~
Flat Bar Shear (W x Thickness) - MS (mm):	460 x 15, 300 x 20
Flat Bar Shear - Blade Length - MS (mm):	465
Flat Bar Shear Work Table Height (mm):	~
Angle Shear 90° - MS (mm):	152 x 152 x 13
Angle Shear 45° - MS (mm):	80 x 80 x 10
Angle Flange Trim (mm):	~
Angle Shear Work Table Height (mm):	~
Round Solid Bar Shear - MS (mm):	Ø45
Square Solid Bar Shear - MS (mm):	45 x 45
Solid Bar Shear Work Table Height (mm):	~
Notching - Rectangle - MS (mm):	50.8 x 90 x 12
Notching Work Table Height (mm):	~
Multi Vee Die Block (mm):	~
Vee Opening Sizes (mm):	~
Max. Tonne Capacity (T):	~
Bending Work Table Height (mm):	~
Motor Power (kW / hp):	7.5 / 10
Voltage / Amperage (V / amp):	415
Nett Weight (kg):	3080



## Description

The Sunrise Punch & Shears are manufactured in Taiwan, also known as Ironworkers are well recognised in our Australian market for the machines being reliable & durable due to their structurally well manufactured unique design & engineering excellence. Sunrise is ISO-9001 certified by BVQI, and our products meet the CE safety requirements and regulations. Sunrise relentlessly seeks continuous improvement and product development to keep a step ahead of their competitors.

The Semi-Automatic CNC positioning tables from SUNRISE are plate and angle positioning systems with touch-screen interfaces. The CNC positioning table is available as a factory-installed option on any dual-cylinder ironworker or punching machine with a 510mm or larger throat depth. The operation and programming are CNC controlled using a pendant mounted controller featuring simple programming and a virtually indestructible design. The operator simply positions the material against the CNC-controlled X and Y stops and initiates the punch program.

The Windows based PC Controller features a 15" Touch-Screen, WiFi and all flash-memory based Nexcom computer. The software provided handles a wide variety of programming needs whilst also being simple to operate.

The double cylinder "S/SD" series have two control foot pedals, & separate operations can be safely performed simultaneously without interference. The low pressure setting for tool change provides maximum operation safety. The long punching cylinder stroke & deep throat enable mounting a wide range of special optional equipment. The large punching base with the "T-slot" fixing provide a solid base for securing the punching tooling, as well as a wide range of optional & custom designed tooling.

The hydraulic system & components that drives the shearing beam & punching head is considerably very quiet compared to most other machines and operates efficiently smooth in all modes. The electrical components & DC control circuit are operated at a low 24 volt system & provides full protection & safety with in the separate key locked cabinet.

The Sunrise machines have proven themselves over & over again to provide trouble free service for many years in production and we have references all around Australia to verify our statement.

## Product Brochure For P175C

### Features

- NC programmable positioning table 1000 x 400mm
  - Stores up to 100 programs and each consisting up to 5 patterns
  - Pre-programmed patterns: line, array, arc and custom
  - Dual hydraulic cylinders allows simultaneous operation without interference
  - Five work stations, Punching, Notching, Plate Shearing, Angle Iron Shearing and Bar Shearing (all stations are guarded)
  - Punching capacity up to 50mm standard
  - Mitre cutting of angle iron
  - Magnetic base halogen lamp
  - Hydraulic system is protected with replaceable filter cartridge
  - Adjustable stroke for faster punching
  - Curved shear blade for minimal job distortion
  - Most cutting blades are four-sided for long life
  - Punch, shear & notching table fitted with stops & guides as standard
  - Two-pedal operation allows two people to work machine to greatly speed up production
  - Adjustable length stop with one-touch electronic backgauge for greater efficiency in repetitious work
- PUNCHING
  - Large hole punching up to Ø50mm as standard
  - Overhang bolster for punching channel & beam flanges
  - Large ruled support table with removable front section for leg down punching in angle or section
  - Easily adjustable stripper & safety guard
- Pre-Commissioning:
    1. Punch & Shear is run & tested prior delivery
    2. Hydraulic oil is included with machine

### Includes

- Full safety guarding at all workstations
- Tooling to all workstations
- Punch, Shear & Notch support tables
- Now with Quick Change Tooling
- 1 metre adjustable "Auto touch length stop" once the material has pushed the micro-switch stop the hydraulic system is activated to shear work piece

### Optional Accessories

- 1000 x 600mm NC Positioning Table
- 3000 x 400mm NC Positioning Table
- PC Based Control Upgrade
- Multi Tool Punch System 30-30-30
- Multi Tool Punch System 30-40-30
- Oil Tank Cooling System

### Specific Features



Machine Capabilities



Includes Length Stop



Flat Bar Shear



Square Bar Shear

Product Brochure For P175C



Round Bar Shear



Angle Shear



Angle Shear



Angle Shear



Angle Shear



Angle Shear



Work Light



Monoblock Design For Rigid Frame Structure



Keyed Punch Ram For Shaped Tool Alignment



Solid Punching Base With T-Slot Grooves



Optional Single Vee Pressbrake Attachment



Optional Multi Vee Pressbrake



Optional Vee Notcher Punch Side



Optional Channel Shear



Optional Hydraulic Holddown for Flat Shear



Optional Pipe Notcher



Product Brochure For P175C




Optional Channel Punching Die Holder




Optional Goose Neck Die Holder



Optional Large Hole Punching



Optional Angle Bending Press



Optional Duplicating Table



Optional Multi Stop Gauge

**Recommended Accessories**

P163

Laser Guide System

P165


Ø6-26mm Round Punch & Dies Set

P166

Ø11-40mm Round Punch & Dies Set

P726

Ø26mm Round Punch - RPN1



Product Brochure For P175C

**P726A**  
Ø26.7mm Round Die - RDN1



**P6005**  
8 x 20mm Slotted Punch



**P6006**  
8.7 x 20.7mm Slotted Die



**P6001**  
8 x 8mm Square Punch




**P6002**  
8.7 x 8.7mm Square Die



**M800**  
Rubber Mat - Anti-Fatigue



**M805**  
Rubber Mat - Anti-Fatigue



**O043**  
Rust & Corrosion Preventive - Penetrant & Lubrication



**O042**  
General Purpose Lubricant & Corrosion Inhibitor



**O044**  
Rust & Corrosion Preventive - Penetrant & Lubrication

