

## Product Brochure For P235

### Coolant Pump & Tank - CPP-20LTR

1/8hp, 240V Motor

10 Litre Plastic Tank & 20 Litres/Min. At 1 Metre Lift



**On Sale**

Ex GST

**\$392.00**

**\$312.17**

Inc GST

**\$450.80**

**\$359.00**

|                                    |                     |
|------------------------------------|---------------------|
| ORDER CODE:                        | P235                |
| MODEL:                             | CPP-20LTR           |
| Type:                              | Coolant Pump & Tank |
| Tank Capacity (Litre):             | 10                  |
| Discharge at 1 metre Lift (L/min): | 20                  |
| Length (L) (mm):                   | ~                   |
| Submerge Depth (L1) (mm):          | ~                   |
| 4 Mount Holes (PCD) (mm):          | ~                   |
| Threaded Outlet (BSPT):            | ~                   |
| A (mm):                            | ~                   |
| B (mm):                            | ~                   |
| C (mm):                            | ~                   |
| D (mm):                            | ~                   |
| E (mm):                            | ~                   |
| F (mm):                            | ~                   |
| G (mm):                            | ~                   |
| H:                                 | ~                   |
| I (mm):                            | ~                   |
| J (mm):                            | ~                   |
| K (mm):                            | ~                   |
| Motor Power (hp):                  | 1/8                 |
| Voltage / Amperage (V / amp):      | 240 / 10            |
| Dimensions (L x W x H) (mm):       | 370 x 310 x 250     |
| Nett Weight (kg):                  | 9                   |

### Description

Manufactured in Taiwan

Plastic coolant tank moulded with divider to help prevent fine swarf particles entering pump

### Features

- 1/8hp 240V motor & PVC tank with 10 litre capacity
- Discharge at 2 metre lift: 20 litres/min, (maximum lift @ 3.5 metres)
- 330mm flexible nozzle with flow tap & magnetic base
- 2 metre PVC clear supply hose
- 1.5 metre PVC clear drain hose
- Safety magnetic On/Off switch
- 1.6 metre power cable from pump to switch
- 2.8 metre power cable from switch to 240V socket
- Removable coolant return particle strain filter
- Coolant tank dimensions: 370 x 250 x 170mm
- Overall height to top of pump 310mm

Product Brochure For P235

**Specific Features**



Left View



Front View



Top View



Rear View



Side View



Flexible Hose with Nozzle



Magnetic Base & Flow Control Valve



Safety Magnetic Switch



Dust & Coolant Proof Switch Cover



Coolant Hose Return



Removable Return Strainer



Return Tank Divider



Coolant Pump Flow Outlet



Min Max Coolant Level Guide

Product Brochure For P235

**Recommended Accessories**

S090A  
Soluble Metal Cutting Fluid - 1  
Litre



S090  
Soluble Metal Cutting Fluid - 5  
Litre



S076  
Cutting Tool Lubricant Fluid -  
500ml



S077  
Drilling, Tapping & Cutting Tool  
Lubricant Spray - 400g



S074  
Cutting Tool Lubricant Paste -  
500g



S091  
Soluble Metal Cutting Fluid - 20  
Litre



H164  
Flexible Coolant Hose



H166  
Flexible Coolant Hose



Product Brochure For P235

---

H170  
Flexible Coolant Hose



P232  
Coolant Pump



P233  
Coolant Pump

