

Product Brochure For S583A

Hydraulic NC Panbrake - PB-820Y

2500 x 2mm Mild Steel Bending Capacity



ORDER CODE:	S583A
MODEL:	PB-820Y
Controller Type:	Digital Single Program
Bending Length (mm):	2500
Mild Steel Capacity (mm):	2
Stainless Steel Capacity (mm):	1.2
Material Clamping Type:	Manual Clamp
Material Bending Type:	Hydraulic Bend
Bending Angle Indicator (deg):	0-125°
Backgauge Travel (mm):	1000
Motor (kW / hp):	3.75 / 5
Voltage / Amperage (V / amp):	415
Floor Space (L x W x H) (mm):	~
Nett Weight (kg):	1700



Features


- 2500mm x 2mm capacity
 - Easy to use single angle programmable control incorporating digital readout for angles from 0-125°
 - Auto cycle: after clamping bottom beam will bend to pre-set angle and return
 - Hydraulic bending with manual material clamp
 - Roving foot pedal incorporates control panel for maximum flexibility
 - Extended fingers allows bending of pans or boxes to a depth of 230mm
 - Ground segmented fingers can be repositioned to suit many applications
 - Heavy duty steel fabricated frame provides accurate bends
 - Safety top beam support stop lever located on right side of machine
 - Quick action beam adjustment for varying material thickness
 - Includes an adjustable rear manual backgauge, also adjustable for tapered material
 - Mild steel capacity is rated on hot rolled material with 250MPA
- Pre-Commissioning:
 1. Panbrake bender is run & tested prior delivery
 2. Hydraulic oil is included with machine

Product Brochure For S583A

Specific Features



Control Panel



Top Beam Support Stop Lever



Removable Fingers



Side View



Roving Foot Controls


Recommended Accessories

M800
Rubber Mat - Anti-Fatigue

M805
Rubber Mat - Anti-Fatigue

O043
Rust & Corrosion Preventive

O042
General Purpose Lubricant & Corrosion Inhibitor



Product Brochure For S583A

O044
Rust & Corrosion Preventive



M977
Digital Bevel Box

