Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For S772

Motorised Plate Curving Rolls - AR-2506

2550 x 6mm Mild Steel Capacity
Initial Pinch Design



ORDER CODE:	S772
MODEL:	AR-2506
Curving System Type:	Initial Pinch
Curving Material Length (mm):	2550
Curving Plate Thickness - Mild Steel (mm):	6
Minimum Rolling Diameter (mm):	400
Roll Diameter (mm):	190
Motor Power (kW / hp):	5.5 / 7.5
Voltage / Amperage (V / amp):	415
Dimensions (LxWxH) (mm):	4160 x 900 x 1200
Floor Space (L x W x H) (mm):	~
Nett Weight (kg):	3200

METALMASTER

1 YEAR WARRANTY

NO PLUG 415V

Features

- Two rolls powered by gearbox and gear system
- Swing out end enables complete cylinder to be removed
- Digital readout display on rear curving roll position
- Motorised up & down rear curving roll
- Heavy duty steel welded mainframes
- Safety wire interlock system with emergency shut-off
- Mobile control panel

- Mild steel capacity is rated on hot rolled material with 250MPA

Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For S772

Specific Features


Left View


Right View


Rear View


Roving Pendant Control


Control Panel




Digital Curving Roll Height Adjustment


Right End View


Swing Out Top Roller


Side View


Motorised Up Down Rear Curving Roll


Safety Wire Interlock System


Initial Pinch Roller Design


Head Rear View


Main Power Isolation Switch


Shown with Optional Ball Transfer Tables Order Code L840