

Product Brochure For S827

Cold Saw, Includes Stand - CS-315C

110 x 70mm Rectangle Capacity

Ø315mm Blade, Single Speed 44rpm

Ex GST **Inc GST**
\$4,014.00 **\$4,616.10**



ORDER CODE:	S827
MODEL:	CS-315C
Cutting Head Action:	Manual
Operation Type:	Swivel - Dual Mitre
Round Capacity @ 90° / 45° (mm):	100 / 90
Square Capacity @ 90° / 45° (mm):	82 / 75
Rectangle Capacity @ 90° / 45° (WxH) (mm):	110 x 70 / 85 x 70
Blade Size - Diametre. x Bore (Ø) (mm):	315 x 32
Vice Clamping Fixture:	Manual
Coolant System:	Yes
Table Working Height (with Stand) (mm):	980
Blade Speed (rpm):	44
Motor Power (kW / hp):	1.8 / 2.5
Voltage / Amperage (V / amp):	240 / 15
Nett Weight (kg):	175



Description

Manufactured in Taiwan

The Hafco MetalMaster manual cold saw consists of a 315mm circular saw blade that runs at a relatively slow speed in conjunction with a coolant system. These cold saws are designed to cut at 90°, or mitre up to 45° in either left or right side of the material simply by releasing the lever located at front of machine. Each machine comes standard with a very heavy and strong cast iron frame base with a cast dual pivot saw head supported by an industrial swivel base system, which makes a MetalMaster cold saw one of the most rugged machines on the market.

The MetalMaster manual cold saw head is well balanced and uses a long actuating handle giving the operator greater leverage and control to guide the saw blade through the work piece of tubing or pipe etc, with ease and utilises a quality head retraction system for returning the cold saw head to the start position. The vice clamps the work piece on both sides of a cut, which extends blade life because the cut off does not drop into the blade.

Features

- Rugged cast iron construction offers years of accurate cutting
- Lock at any angle between -45° or +45° mitre in both directions via locking lever
- Degree markings engraved onto swivelling base for quick and accurate mitre cutting
- Dual material clamp system providing burr free cuts on both pieces of material
- Quick action vice clamp lever designed to increase production
- Built in blade coolant pump system with flow control valve
- Oil sight glass located on right side of the gearbox so operator can maintain correct lubrication levels according to specifications provided
- Dead man trigger switch located on cutting handle provides operator safety on/off power control
- Automatic retract safety blade guard covers blade when returned to home position
- Spring assisted head return provides a even balance during cutting operation and reduces operator fatigue
- HSS cutting blade is included for general types of material and thickness

Includes

- Blade
- Stand
- Coolant system
- Material length stop

Product Brochure For S827

Specific Features




Control Panel




Head Shown at 45 Degrees



Adjustable Cut Length Stop



Swivel Head Degree Scale NEW



Swivel Head Lock Lever



Heavy Duty head Pivot Hinge



Adjustable Vice Jaws



Deadman Trigger Switch



Coolant Pump and Tank



Collant Flow Control Valve



Side View

Product Brochure For S827

Recommended Accessories

S092

BROBOLUBE Industrial Gearbox Oil



S158

HSS Cold Saw Blade



S158A

HSS Cold Saw Blade



S158B

HSS Cold Saw Blade



S158C

HSS Cold Saw Blade



S158D

HSS Cold Saw Blade



S158E

HSS Cold Saw Blade



S158J

HSS Cold Saw Blade



Product Brochure For S827

S158M
HSS + COBALT Cold Saw
Blade



S158S
HSS + COBALT Cold Saw
Blade



S158X
HSS + COBALT Cold Saw
Blade



S090A
Soluble Metal Cutting Fluid - 1
Litre



S090
Soluble Metal Cutting Fluid - 5
Litre



S076
Cutting Tool Lubricant Fluid -
500ml



S077
Drilling, Tapping & Cutting Tool
Lubricant Spray - 400g



S074
Cutting Tool Lubricant Paste -
500g



S091
Soluble Metal Cutting Fluid - 20
Litre



L300
Magnetic Swarf Remover



M9991
Magnetic Floor Sweeper



L812
Roller Conveyor



Product Brochure For S827

L814
Roller Conveyor Stand



W343
Roller Stand



W343A
Roller Stand



W3434
Roller Stand




W3436
Roller Stand - V-Type



M800
Rubber Mat - Anti-Fatigue



M805
Rubber Mat - Anti-Fatigue



O043
Rust & Corrosion Preventive



O042
General Purpose Lubricant & Corrosion Inhibitor



O044
Rust & Corrosion Preventive



S812
Coolant Pump

