Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For S902G

Hydraulic NC Pressbrake - PB-70B

70T x 3200mm - Includes Light Curtain Safety Guarding
Estun NC-E21 Control 2-Axis with Ballscrew Backgauge



ORDER CODE:	S902G
MODEL:	PB-70B
Control Unit (Type):	Estun NC-E21
Nominal Pressure - Tonnage (Ton):	70
Nominal Pressure - Kilonewtons (kN):	630
Length of Work Table (mm):	3200
Distance Between Columns (mm):	2650
Throat Depth (mm):	250
Maximum Open Height (mm):	360
Ram Stroke (mm):	100
Machine Axis (No.):	2
Safety Guarding System (Type):	Light Curtain System
Backgauge Travel (mm):	520
Table Bed Crowning System (Type):	~
Motor Power (kW / hp):	5.5 / 7.5
Motor Voltage (V):	415
Floor Space Requirements (L x W x H) (mm):	3900 x 1900 x 2400
Nett Weight (kg):	5740

METALMASTER

1 YEAR WARRANTY

NO PLUG 415V

Description

MetalMaster Quality Pressbrakes feature high durability, and provide precision bending capabilities. The Pressbrake main frames are constructed from rolled, stress relieved solid steel to prevent distortion during the bending process and under extreme continuous loads.

MetalMaster Pressbrakes are produced in a high volume production process and therefore are able to be manufactured cost effectively, resulting in affordable price, representing value for money and quicker return on investment.

Featuring an adjustable synchronised torsion bar with positive stop system ensures consistent and accurate bending beam parallelism tolerance to 0.01mm via the digital Control unit.

All electrical components are of European quality supplied by, Telemecanique, Merlin Gerin and ABB.

Features

- Hydraulic / Mechanical ram, synchronised positive stop design, ram stroke controlled by precision mechanical nut depth stops built into each cylinder. Electronically controlled by Estun NC-E21 digital control assuring accurate repeatability.
- Parallelism is ensured by torsion bar that can be easily adjusted by clutch system.
- Estun NC-E21 programmable digital control stores up to 40 unique programs with 25 automatic progressive bending steps in each individual program, assuring production accuracy & repeatability every time.
- Estun NC-E21 programmable hardened ballscrew backgauge system, simply enter the desired measurement into the controller and press go, the backgauge then will move quickly into the position you have requested. The superior hardened ballscrew system eliminates any backlash that leadscrew type machines produce.
- Segmented heavy duty 35° offset top punch is segmented for return bend clearance, complete with European style punch holder with an adjustable wedge clamping system for crowning. Intermediate clamp has safety key to stop punch dropping.
- Multi vee ('V') bottom die is made from one 3200mm solid die block design to handle heavy plate, safety edge vee ('V') is incorporated in bottom die block.
- Conveniently mounted control box on pendant for quick swivel and adjustments.
- Mono-block steel frame design, welded then machined to ensure minimal bed deflection under load
- Enclosed rear gate with micro safety switches complete with sliding rear door for easy access.
- European Style Intermediate clamping system, allowing operator to change position of tooling to suit multiple requirements on complex applications. This feature ensures minimum down time, more productivity and results in reduced cost per finished product.
- Sliding steel fabricated sheet supports enabling a wide range of material sizes to be aligned and supported at the correct required height. This feature is achieved with a "T" slot machined down the total length of the die bed; sheet supports are also adjustable vertically to assist in supporting material with return bends already folded.
- Adjustable sliding blocks control the machines beam to provide desirable open height distance to the (slow speed) mute bending point. Operator adjustable locking knobs for quick adjustment, enables accurate repeatability and increased productivity.

Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For S902G

- Metal safety guarding surrounding the machine with rear sliding door fitted and micro switch ensuring operator safety. Clear access panels placed at each end of machine allows the operator to clearly view tooling and work piece during bending operation. MetalMaster specially design gates to suit Australian safety requirements.
- Hydraulic MPA pressure gauge mounted on right side of support frame with quick adjusting pressure control knob allowing operator to accurately set the pressure required for different material thickness, incorporating with hydraulic overload protection.
- Welded steel fabricated synchronised torsion bar horizontally supporting main bending beam to provide consistent parallelism that also can be adjusted for taper correction.
- The vertical supporting slides are treated to provide greater ware resistance and increased accuracy.
- Includes safety control guarding system with light curtains fitted
- Mild steel capacity is rated on hot rolled material with 250MPA

- Pre-Commissioning:
- 1. Pressbrake is run & tested prior delivery
- 2. Hydraulic oil is included with machine

Includes

- Operated by ESTUN NC- E21 control mounted on a swivel pendant for optimal ergonomics
- LED superior bright work lights provides clearer view to workpiece
- Sliding front sheet support arms
- Emergency stop buttons conveniently located on control panel and foot control
- Mobile dual operation foot control
- Segmented 35° offset top toolingh
- Solid one piece four way multi vee (V) die block
- Top tooling tool intermediate holder system with wedge type adjustment
- Premium linear way side mount ballscrew backgauge with 520mm travel
- Metal constructed safety guarding surrounding machine with clear side viewing panels
- Integrated hydraulic system allowing rapid approach switching automatically to slow bend

Specific Features



Left View



Right View



Laser Guarding in Use


NC Estun E21 Controller




NC Estun E21



Adujstment Travel Control



Enclosed Rear Safety Guarding


Top and Bottom Tooling

Auckland: (09) 2717 234
Christchurch: (03) 741 6241


sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For S902G


Adjustable and Sliding Front Sheet Supports


Intermediate Clamps


Adjustable Top Tool Taper Wedge System



Fine Adjustment Beam Positioning



Fine Adjust Back Gauge


Synchronised Torsion Bar


Estun NC E21 Control Back Gauge




Adjustable Pressure Control



Mobile Foot Control




Mobile Foot Control Top Buttons




Lubrication Chart



Tonnage Calculation Chart


Segmented Top Punch



One Piece 4 Sided Die



Shown with Optional Ball Tansfer Tables

Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For S902G

Recommended Accessories

S988

Quick Action Intermediate Clamps



S990S

35º Top Punch Pressbrake Tooling - Segmented



S990

35º Top Punch Pressbrake Tooling




S990F

35º Top Punch Pressbrake Tooling



S9927

75mm Die Block Pressbrake Tooling



S991S

86º Top Punch Pressbrake Tooling - Segmented



S991

86º Top Punch Pressbrake Tooling



S996

15º Top Punch Pressbrake Tooling




Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For S902G

S996A
60mm Die Block Pressbrake Tooling



S996B
60mm Die Rail Pressbrake Tooling



Q200
Combination Set



Q200A
Combination Set




Q201
Universal Bevel Protractor



Q2105
Digital Height Gauge



M970
Digital Angle Rule



M972
Digital Angle Rule




M974
Digital Angle Rule



M800
Rubber Mat - Anti-Fatigue



M805
Rubber Mat - Anti-Fatigue



O043
Rust & Corrosion Preventive



Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For S902G

O042

General Purpose Lubricant & Corrosion Inhibitor



O044

Rust & Corrosion Preventive

