

Product Brochure For S923

Hydraulic NC Guillotine - HG-460B

1300 x 6mm Mild Steel Shearing Capacity

1-Axis Ezy-Set NC-89 Controlled Backgauge & Includes Rapid Blade Adjustment



| | |
|--------------------|--------------------|
| Ex GST | Inc GST |
| \$18,606.00 | \$21,396.90 |

| | |
|--|--------------------|
| ORDER CODE: | S923 |
| MODEL: | HG-460B |
| Shearing Capacity - Mild Steel (mm): | 6 |
| Shearing Capacity - Stainless Steel (mm): | 4 |
| Shearing Length (mm): | 1300 |
| NC Control (Type): | Ezy-Set NC-89 |
| Backgauge (Type): | Leadscrew |
| Backgauge Travel (mm): | 700 |
| Pneumatic Sheet Supports: | ~ |
| Quick Action Blade Clearance Adjustment: | Yes |
| Strokes / min (SPM): | 12 |
| Blade Angle (deg): | 2° |
| Throat Depth (mm): | ~ |
| Motor Power (kW / hp): | 5.5 / 7.5 |
| Voltage / Amperage (V / amp): | 415 |
| Floor Space Requirements (L x W x H) (mm): | 1990 x 2230 x 1312 |
| Nett Weight (kg): | 2046 |



Features

- 1300mm x 6mm cutting capacity
 - 5.5kW / 7.5hp 415V motor
 - Ezy-Set NC-89 Go-To digital display controlled backgauge with DRO counter
 - Quick action blade clearance adjustment for shearing material 1 - 6mm
 - Hydraulic material clamping for accurate shearing
 - One shot lubrication pump & reservoir for slideway protection
 - Blades made from 9CrSi material suitable for cutting stainless steel
 - Transfer balls inserted into work table allowing larger sheets to be easily positioned to the cut position and squaring arm
 - Front sheet supports with ball bearing guides preventing material damage when setting up
 - Three safety photo electric light beams on rear guarding
 - Safety reset rear guarding button mounted to back of electrical box
 - Heavy duty under driven machine construction
 - Equipped with shadow line lighting-alignment device
 - Roving foot pedal control
 - Mild steel capacity is rated on hot rolled material with 250MPA
- Pre-Commissioning:
 1. Guillotine is run & tested prior delivery
 2. Hydraulic oil is included with machine

Product Brochure For S923

Specific Features



Right View



Rear View



NC 89 Control Panel



NC 89 Backgauge DRO



Squaring Arm with Measuring Scale



Material Transfer Balls On The Table



Front Sheet Supports with Roller Bearings




3 Safety Photo Sensors



Quick Action Blade Clearance Adjustment



One Shot Lubrication



Roving Foot Pedal with Emergency Stop

Product Brochure For S923



Recommended Accessories

S9981
1320mm Sheet Metal Guillotine
Blade Set - 9CrSi

M800
Rubber Mat - Anti-Fatigue

M805
Rubber Mat - Anti-Fatigue

O043
Rust & Corrosion Preventive



O042
General Purpose Lubricant &
Corrosion Inhibitor

O044
Rust & Corrosion Preventive

