Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For S926

Hydraulic Guillotine - HG-840M

2500 x 4mm Mild Steel Shearing Capacity
Manual Backgauge & Includes Rapid Blade Adjustment



ORDER CODE:	S926
MODEL:	HG-840M
Shearing Capacity - Mild Steel (mm):	4
Shearing Capacity - Stainless Steel (mm):	2.5
Shearing Length (mm):	2500
NC Control (Type):	~
Backgauge (Type):	Manual
Backgauge Travel (mm):	760
Pneumatic Sheet Supports:	~
Quick Action Blade Clearance Adjustment:	Yes
Strokes / min (SPM):	12
Blade Angle (deg):	2º
Throat Depth (mm):	~
Motor Power (kW / hp):	5.5 / 7.5
Voltage / Amperage (V / amp):	415
Floor Space Requirements (L x W x H) (mm):	~
Nett Weight (kg):	2590

METALMASTER

1 YEAR WARRANTY

NO PLUG 415V

Features

- 2500mm x 4mm cutting capacity
- 5.5kW / 7.5hp 415V motor
- Quick action blade clearance adjustment for shearing material 1 - 4mm
- Hydraulic material clamping for accurate shearing
- One shot lubrication pump & reservoir for slideway protection
- Manual backgauge with digital scale display unit
- Roving foot pedal control
- Clamp beam design allows clear view to shadow line on material
- Blades made from 9CrSi material suitable for cutting stainless steel
- Transfer balls inserted into work table allowing larger sheets to be easily positioned to the cut position and squaring arm
- Front sheet supports with ball bearing guides preventing material damage when setting up
- Safety three safety photo electric light beams on rear guarding
- Safety reset rear guarding button mounted to back of electrical box
- Heavy duty under driven machine construction
- Equipped with shadow line lighting-alignment device
- Mild steel capacity is rated on hot rolled material with 250MPA

- Pre-Commissioning:
- 1. Guillotine is run & tested prior delivery
- 2. Hydraulic oil is included with machine

Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For S926


Specific Features



Front View



Control Panel



Cut Stroke Adjustment Dial




Quick Action Blade Clearance Adjustment Operation




Quick Action Blade Clearance Adjustment Swivel Handle


Quick Action Blade Clearance Adjustment


Squaring Arm


Squaring Arm with Measuring Scale


Front Sheet Supports


Front Sheet Supports with Roller Bearings


Material Transfer Balls on the Table


Manual Back Gauge


Backgauge with Digital Readout


Backgauge Scale for Digital Readout



Backgauge Digital Readout


3 Safety Electric Photo Sensors

Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For S926


Safety Omron E3ZS Rear Light Sensor Guarding


One Shot Lubrication


Rear Guard Reset Button



Mobile Foot Control


Emergency Stop Switch


Shown with Optional Ball Transfer Tables - Order Code (L840)

Recommended Accessories


S9982
2540mm Sheet Metal Guillotine Blade Set - 9CrSi



M800
Rubber Mat - Anti-Fatigue



M805
Rubber Mat - Anti-Fatigue



O043
Rust & Corrosion Preventive



Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For S926

O042

General Purpose Lubricant & Corrosion Inhibitor



O044

Rust & Corrosion Preventive

