

## Product Brochure For S970GL

# Hydraulic NC Pressbrake - PB-40B

44T x 2000mm -

Includes Laser Safety Guarding with Ballscrew Backgauge



**Ex GST**                      **Inc GST**  
**\$29,830.00**    **\$34,304.50**

|  |                    |
|--|--------------------|
| ORDER CODE:                                | S970G              |
| MODEL:                                     | PB-40B             |
| Control Unit (Type):                       | Estun NC-E21       |
| Nominal Pressure - Tonnage (Ton):          | 44                 |
| Nominal Pressure - Kilonewtons (kN):       | 400                |
| Length of Work Table (mm):                 | 2000               |
| Distance Between Columns (mm):             | 1615               |
| Throat Depth (mm):                         | 200                |
| Maximum Open Height (mm):                  | 330                |
| Ram Stroke (mm):                           | 100                |
| Machine Axis (No.):                        | 2                  |
| Safety Guarding System (Type):             | Laser System       |
| Backgauge Travel (mm):                     | 520                |
| Table Bed Crowning System (Type):          | ~                  |
| Motor Power (kW / hp):                     | 4 / 5.3            |
| Motor Voltage (V):                         | 415                |
| Floor Space Requirements (L x W x H) (mm): | 2700 x 1800 x 2400 |
| Nett Weight (kg):                          | 3800               |

METALMASTER



## Description

MetalMaster Quality Pressbrakes feature high durability, and provide precision bending capabilities. The Pressbrake main frames are constructed from rolled, stress relieved solid steel to prevent distortion during the bending process and under extreme continuous loads.

MetalMaster Pressbrakes are produced in a high volume production process and therefore are able to be manufactured cost effectively, resulting in an affordable price, representing value for money and quicker return on investment.

All electrical components are of European quality supplied by, Telemecanique, Merlin Gerin and ABB.

## Features

- ESTUN E21 NC Controller
- Stores up to 40 programs with 25 bending steps per program
- Position control of Backgauge
- Backgauge retract function
- Bottom stroke dwell timer
- Work piece counting
- One-key backup / restore
- LCD Display
- LASER GUARDING -
- Laser guarding provides close proximity operator protection allowing faster bending cycles, promoting higher productivity
- The Laser system is compliant with requirements of EN61496-1, EN61496-2, ISO 13849-1 Plc, as well as AS/NZS 4024.1503
- Australian designed electrical system featuring dual channel monitoring on all essential machine functions
- Top beam speed & stopping performance are all real time monitored to ensure compliance with safety regulations
- METALMASTER Pressbrakes -
- Dual Hydraulic rams balanced by a heavy duty torsion bar, Electronically controlled by the E21 NC control assuring accuracy & repeatability.
- Back gauge with linear guides & ballscrew provides fast and accurate positioning
- Segmented heavy duty 35° top punch
- European style punch holder with an adjustable wedge clamping system for crowning
- Multi vee ('V') bottom die is made from one solid 2000mm die block design to handle heavy plate, safety edge vee ('V') is incorporated in bottom die block.
- Sliding steel fabricated sheet supports enabling a wide range of material sizes to be aligned and supported at the correct required height.

## Product Brochure For S970GL

This feature is achieved with a "T" slot machined down the total length of the die bed, sheet supports are also adjustable vertically to assist in supporting material with return bends already folded.

- Metal safety guarding surrounding the machine with rear sliding door fitted with micro switch ensuring operator safety.
  - Hydraulic pressure gauge with quick adjust pressure control & over pressure protection allows the operator to accurately set the pressure required for different material thickness.
  - The vertical supporting slides are treated to provide greater wear resistance and increased accuracy.
  - Reinforced side frames providing addition support strength to machine throat
  - Includes laser guarding system
  - Mild steel capacity is rated on hot rolled material with 250MPa
- Pre-Commissioning:
    1. Pressbrake is run & tested prior delivery
    2. Hydraulic oil is included with machine

### Includes

- ESTUN NC- E21 control mounted on a swivel pendant for optimal ergonomics
- LED superior bright work lights provides clearer view to workpiece
- Sliding front sheet support arms
- Mobile dual operation foot control
- 35 Degree Top Punch with Segments (3x500, 1x200, 2x100, 1x50, 1x40, 1x10)
- Top tooling tool intermediate holder system with wedge type adjustment
- Multi V bottom die block 75 x 75mm with a range of V's between 4mm~40mm
- Ballscrew backgauge with 520mm travel
- Metal constructed safety guarding surrounding machine

### Specific Features



Enclosed Rear Safety Guarding




NC Estun E21 Controller




NC Estun E21



Left Laser



Right Laser



Laser Alignment Guide



Adjustable Travel Limit Control



Laser Guarding system In Use



Product Brochure For S970GL

---

**Recommended Accessories**

S989

35° Top Punch Pressbrake Tooling



S989S

35° Top Punch Pressbrake Tooling - Segmented



Q201

Universal Bevel Protractor



M800

Rubber Mat - Anti-Fatigue



M805

Rubber Mat - Anti-Fatigue

