Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For T061A

Tube Bender - Manual - 11BH-M

Ø12 - Ø40mm Round Capacity



ORDER CODE:	T061A
MODEL:	11BH-M
Material (Type):	Tube
Material Section (Type):	Round
Machine (Type):	Manual
Hydraulic Jack Size (Tonne):	~
Round Pipe Range (NB) - Mild Steel (inch / mm):	~
Round Tube Range (OD) - Mild Steel (inch / mm):	Ø12 - Ø40mm
Square Tube Range (inch / mm):	~
Tube Wall Thickness - Mild Steel (inch / mm):	~
Round Pipe (NB) x Wall Capacity - Mild Steel (inch):	~
Round Pipe (NB) x Wall Capacity - Aluminium (inch / mm):	~
Round Pipe (NB) x Wall Capacity - Stainless Steel (inch / mm):	~
Round Tube (OD) x Wall Capacity - Mild Steel (inch / mm):	~
Round Tube (OD) x Wall Capacity - Aluminium (inch / mm):	~
Round Tube (OD) x Wall Capacity - Copper, Brass (inch / mm):	~
Round Tube (OD) x Wall Capacity - Stainless Steel (inch / mm):	~
Round Tube (OD) x Wall Capacity - Chromoly (inch / mm):	~
Solid Rod - Mild Steel (inch / mm):	~
Square Tube x Wall Capacity - Mild Steel (inch / mm):	~
Rectangle Tube x Wall Capacity - Mild Steel (inch / mm):	~
Bend Speed - Maximum (Deg / Sec):	~
Bend Direction:	~
Centre Line Radius - Maximum (CLR) (inch / mm):	~
Centre Line Radius - Minimum (CLR) (inch / mm):	~
Tube Formers Included (inch / mm):	12, 16, 20, 25, 32, 40mm
Pipe Formers Included (inch / mm):	~
Spigot Size on Ram (inch / mm):	~
Angle Capacity (deg):	~
Hydraulic Pressure - Maximum (psi):	~
Motor Power (kW / hp):	~
Voltage / Amperage (V / amp):	~
Nett Weight (kg):	105

Description

The 11B and 11BH models are Universal Draw Bender type designed to form presision bends using mild steel, or non-ferrous materials in either tube or section forms.

Features include slide block pressure applied by cam action clamp, tube clamping by quick action cam lock giving ease & speed of operation plus rapid setting up times for short run production.

Made in Australia

Other models also available

Features

- Engineered from the highest quality materials
- Simple setup and operation
- Bench mounted
- Hand operated
  Slide block pressure applied by cam action clamp

Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For T061A

- Tube clamping by quick action cam lock, giving ease and speed of operation
- Round tube capacity 40mm x 3mm, 40mm x 1.6mm
- Maximum angle of Bend 180 degrees
- Maximum radius 228mm Centre Line Radius
- Overall dimensions 76cm long x 84cm wide x 14cm high
- Weight approximately 85kg

STANDARD RADIUS FORMERS

Former Size	Centre Line Radius
12mm (1/2")	45mm (1 3/4")
16mm (5/8")	55mm (2 1/4")
20mm (3/4")	65mm (2 1/2")
25mm (1")	75mm (3")
32 mm (1 1/4")	125mm (5")
40mm (1 1/2")	150mm (6")

Specific Features



Top View

Recommended Accessories

M977
Digital Bevel Box

