Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For T070

Tube Bender - Electric - DB-32

Ø15.87 - Ø31.75mm Round Tube Capacity
Includes Ø15.87, Ø19.05, Ø22.22, Ø25.4 & Ø31.75mm Aluminium Tube Formers

Ex GST	Inc GST
$2,916.00	$3,353.40



ORDER CODE:	T070
MODEL:	DB-32
Material (Type):	Tube
Material Section (Type):	Round
Machine (Type):	Electric
Hydraulic Jack Size (Tonne):	~
Round Pipe Range (NB) - Mild Steel (inch / mm):	~
Round Tube Range (OD) - Mild Steel (inch / mm):	Ø15.87 - Ø31.75
Square Tube Range (inch / mm):	~
Tube Wall Thickness - Mild Steel (inch / mm):	2.0*
Round Pipe (NB) x Wall Capacity - Mild Steel (inch):	~
Round Pipe (NB) x Wall Capacity - Aluminium (inch / mm):	~
Round Pipe (NB) x Wall Capacity - Stainless Steel (inch / mm):	~
Round Tube (OD) x Wall Capacity - Mild Steel (inch / mm):	~
Round Tube (OD) x Wall Capacity - Aluminium (inch / mm):	~
Round Tube (OD) x Wall Capacity - Copper, Brass (inch / mm):	~
Round Tube (OD) x Wall Capacity - Stainless Steel (inch / mm):	~
Round Tube (OD) x Wall Capacity - Chromoly (inch / mm):	~
Solid Rod - Mild Steel (inch / mm):	~
Square Tube x Wall Capacity - Mild Steel (inch / mm):	~
Rectangle Tube x Wall Capacity - Mild Steel (inch / mm):	~
Bend Speed - Maximum (Deg / Sec):	~
Bend Direction:	~
Centre Line Radius - Maximum (CLR) (inch / mm):	~
Centre Line Radius - Minimum (CLR) (inch / mm):	~
Tube Formers Included (inch / mm):	15.87, 19.05, 22.22, & 25.4 & 31.75 OD Round
Pipe Formers Included (inch / mm):	~
Spigot Size on Ram (inch / mm):	~
Angle Capacity (deg):	0 - 180º
Hydraulic Pressure - Maximum (psi):	~
Motor Power (kW / hp):	1.7 / 2.3
Voltage / Amperage (V / amp):	240
Nett Weight (kg):	32.6

Description

Manufactured in Taiwan

A versatile, powerful and portable tube-bending system for site use or pre-fabrication of pre-set angle

The DB-32 includes a digital display readout for dialling in the bend angle required and is use on the following material tube types; Steel, copper, plastic-coated copper, coated soft steel, aluminium. Universal applications for plumbing, heating, refrigeration, air conditioning and general industry.

Features

- Complete with 5 Aluminium round tube formers (Ø15.87, Ø19.05, Ø22.22, Ø25.4 & Ø31.75mm OD)
- Digital readout display 0-180º for repetitive bends
- Automatic stop at pre-selected angle
  High reduction transmission for increased torque

Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For T070

- Patented low-friction guide shoe
- Forward & reverse switch
- 1.7kW 240V motor

- Aluminium Round Tube Formers Capacities:
- Ø15.87, Ø19.05, Ø22.22, Ø25.4mm OD - 2.0mm mild steel wall & 1.6mm stainless steel wall thickness
- * Ø31.75mm OD - 1.6mm mild steel wall & 1.2mm stainless steel wall thickness

Includes

- Aluminium Round Tube Formers:
- Ø15.87mm OD x 68mm Centreline radius
- Ø19.05mm OD x 80mm Centreline radius
- Ø22.22mm OD x 92mm Centreline radius
- Ø25.4mm OD x 103mm Centreline radius
- Ø31.75mm OD x 130mm Centreline radius

- Three leg stand
- Plastic carry case

Specific Features


Plastic Carry Case



Digital Readout Angle 0~180º


Main Body Top View



Forward Reverse Switch


Bend Angle Setting Dial For Digital Readout


Bending Trigger Switch


Formers-Follower Dies


1" Inch Former & Follower Die


Former & Follower Die Side View

Auckland: (09) 2717 234
Christchurch: (03) 741 6241

sales@machineryhouse.co.nz
www.machineryhouse.co.nz

Product Brochure For T070

Recommended Accessories

T072
28.57mm OD Round Tube Former Set



W3436
Roller Stand - V-Type



T606
Electric Pipe & Tube Bender - Digital Control



T607
Electric Pipe & Tube Bender - Digital Control, Includes Stand



B8119
Pipe/Tube Bending Lube - 475ml



M977
Digital Bevel Box

