

Product Brochure For V341

Safeway Pneumatic Production Vice - PQV-130V

130mm Jaw Width

140mm Jaw Opening



ORDER CODE:	V341
MODEL:	PQV-130V
D - Jaw Width (mm):	130
J - Jaw Opening (mm):	140
K - Jaw Height (mm):	55
Power (kgf):	0-1500
Air Pressure (kg/cm2):	1.5-7.0
Stroke (mm):	0-3
A (mm):	482
B (mm):	405
C (mm):	102
E (mm):	152
F (mm):	150
G (mm):	100
H (mm):	15
I (mm):	115
L (mm):	95
M (mm):	14
N (mm):	18
X (mm):	65
Y (mm):	100
Dimensions (L x W x H) (mm):	665 x 250 x 205
Nett Weight (kg):	38



Description

Designed for production applications with simple ON/OFF operation.

Features

- Robust construction of one piece casting consisting of fixed jaw and vise bed
- Rigid casting of high tensile ductile iron FCD60JIS (Equal to GGG60) with 60kgs/mm2 or 80,000 psi tensile strength
- Suitable for mass production runs on machine centre's, milling machines, drilling machines or special purpose machines
- Compact pneumatic mechanism design. No oil is required only a air supply
- Compact total length of vice with Max. clamping capacity
- Safety locking mechanism for unexpected termination of air supply. After pneumatic clamping. The work piece will be remain clamped firmly even without the air supply
- Easy and simple ON-OFF switch control for pneumatic operation
- Safety protection with Max. pneumatic clamping stroke is 4mm to prevent inserting operator's finger during clamping operation. (Stroke is 2mm best power capacity)
- Rapid ON-OFF only 1.5sec
- Free adjusting of Max. pneumatic clamping pressure from 0-1000kgf (4000) by air regulator, jaw opening 2mm is best clamping power capacity of workpiece
- Vise bed flange hardened to HRC45° to reduce up wear and maintain accuracy
- Down trust "semi-spherical segment" mechanism eliminates the jaw and work-piece lifting