

Product Brochure For W016

Auto Darken Welding Helmet - 6~9 / 9~13 Shade - TEC-4G

Suits Mig, Tig, Arc, Plasma & Grinding

Includes Grinding & Oxy Function



TECMEN[®]



Features

- Suitable for MIG, TIG, Plasma, Arc welders, Grinding & Oxy cutting
- Adjustable shade from 6~9 / 9~13
- Huge viewing area 95 x 85mm
- Automatic activation in 1/25,000 second
- Solar powered with 4 arc sensors (inc. 1 x CR2450 lithium battery)
- Adjustable sensitivity dial with grinding function
- Adjustable delay time dial
- Protects from UV and IR radiation
- Light weight high impact resistance nylon
- AS/NZS 1338.1.1992

Includes

- Includes 1 x additional lens cover & sweatband

ORDER CODE:	W016
MODEL:	TEC-4G
Viewing Area (mm):	95 x 85
Cartridge Size (mm):	133 x 114 x 9
Arc Sensors (No.):	4
Light State:	DIN 3.5
Shade:	Dual range 6 ~ 9 / 9 ~ 13
Shade Control:	Internal Variable Shade
Power On/off:	Fully Automatic
Sensitivity Control:	Low-High by Dial Knob
UV/IR Protection:	Up to DIN 16 at all times
Helmet Power Supply:	Solar Cell, Battery Change & Required (1 x CR2450 & lithium battery)
Respirator Power Supply:	~
Switching Time Light To Dark:	1/25,000 seconds
Delay Time Dark To Light (Seconds) (sec):	0.1 ~ 1.0 (via Dial Knob)
TIG Rated Minimum (amp):	2
Grinding Function (Yes / No):	YES
Inactive Shade (Grind/Off):	~
Operating Temperature:	-10°C ~ +55°C
Storing Temperature:	-20°C ~ +70°C
Helmet Material:	High Impact & Resistant Nylon
Application Range:	Stick, Mig, Tig, Arc Welding, & Grinding, Plasma & Oxy Cutting
Standard:	AS/NZS 1338.1.1992
Total Weight (grams):	490

Product Brochure For W016

Specific Features



Front View



Left View



Top View




Back View



Angle Adjustment



Sensitivity Delay and Shade Switches



Shade Switch



Delay Sensitivity and Shade Switches



Includes Additional Lens Cover and Sweatband

Product Brochure For W016

Recommended Accessories

W001

Auto Darken Welding Helmet -
9-13 Shade



W002

Auto Darken Welding Helmet -
9-13 Shade

