

Product Brochure For W07725A

2550 x 1250mm BuildPro Max Modular Welding Table - Nitrided Finish - TMQD626125F

Reversible Table Plates
Ø16mm Holes

Limited Stock

Ex GST **Inc GST**
\$9,626.00 **\$11,069.90**



ORDER CODE:	W07725A
MODEL:	TMQD626125F
Table Top Finish (Type):	BuildPro Max Table
Table Top Size (mm):	2550 x 1250
Table Height (mm):	900
Table Side Height (mm):	~
Top Plate Thickness (mm):	16
Grid Pattern (mm):	50 x 50
Table Hole Diameter (Ø):	16
Table Slots (mm):	~
Static Load Capacity (kg):	3000
Total W.L.L. (kg):	~
Number of Legs (No.):	~
Nett Weight (kg):	654

BuildPro™



Description

BuildPro® Models

NEW REVERSIBLE SELF-LOCATING TABLE PLATES!

Get longer wear from your BuildPro® Table.

When the surface of your BuildPro® Table plates show signs of wear, turn them over to provide a new work surface. New, Patented Bushing design allows you to remove, re-position, re-align, and reverse the table plates!

The very practical, modular design of the BuildPro® Table makes it easy to set-up and tear down for job at hand, big or small. Save time and money by holding, positioning and locating quickly and easily with a wide variety of BuildPro® clamps and accessories.

In this economy, we know you need to be flexible and responsive to new business opportunities by reducing set-up time, improving consistency and work quality and remaining competitive in both pricing and delivery in a wide variety of jobs; short runs, volume production, prototypes, and multiple jobs in fabrication, repairs, and maintenance.

Accuracy:

Table flatness : 0.30mm / 914.4mm
Hole diameter : 16mm + 0.05mm
Hole spacing : 50mm ± 0.038mm
Plate thickness : 16mm ± 0.10mm

All BuildPro® Max Tables have 16mm thick steel plate with Ø16mm holes in a 50mm grid pattern.

The New BuildPro MAX has a continuous plate tabletop surface with 33% more machined holes than the standard, slotted BuildPro Tables, for a maximized work surface.

Use the BuildPro MAX to: Set-up heavy duty, large, or complex fixtures, or set-up more than one fixture at a time. Utilize the additional holes for clamping at multiple points for greater fixturing accuracy.


Features

- The nitriding (heat-treating) process is a mechanical polish and post salt bath oxidative treatment. The benefits of this process included: Anti-Spatter, Corrosion Protection, and Resistance to wear, lubricity and fatigue strength
- Ø16mm holes
- 16mm thick plate
- 50 x 50mm grid pattern

Product Brochure For W07725A

- 900mm table height
- Includes legs

Specific Features



33 Percent more CNC Machined Holes




Set Up Heavy Duty Large or Complex Fixtures




Shown with Optional Clamps Fixtures



Shown with Optional Clamps Fixtures Close Up



Shown with Optional Clamps Fixtures Setup



Shown with Optional Clamps Fixtures Setup CloseUp

Recommended Accessories

C103

228mm Multi-Purpose Locking Clamp



W08512

Weld Clamps with Locking Nuts (2 Piece Pack)



W08515

38mm x M12 Multi-Purpose Riser/Stops (Spigot Type) - 4pc Pack



W07748

BuildPro Levelling Caster - 1 Piece



Product Brochure For W07725A

W07772

BuildPro Modular Fixturing Kit

