

Product Brochure For W171A

Air Cooled TIG Welding Torch - SR17-4MCP50

35/50 Connector

4 Metre



ORDER CODE:	W171A
MODEL:	SR17-4MCP50
Lead Length (m):	4
Connector Type:	35/50
Connector Size (mm):	Ø12
Maximum Amp Rating (amp):	150



Description

The SR17 TIG Torch has been engineered for trouble-free and superior performance during AC and DC High Frequency TIG welding. The ergonomically designed lightweight handle includes soft grips, knuckle joints and a screwless, interchangeable switch. Rubber cable materials guarantee optimal cable performance, whilst the shielded switch leads ensure minimal tracking and maximum machine protection. This torch is also 'flex-head' compatible.

Features

- Adjustable amperage control on torch
- 35-50mm Dinse style connections
- **ERGONOMIC HANDLE** - Like an extension of your hand, the ergonomically designed handle includes soft grips, knuckle joints and a screwless, interchangeable switch.
- **ADVANCED CABLE SYSTEM** - UNIMIG's advanced cable system features rubber cable materials to guarantee the best performance. Switch leads are shielded as standard to ensure minimal tracking and maximum machine protection. Positioning of the torch is made easier through the combination of knuckle joints and a flexible leather section that covers the first metre of the torch behind the handle.
- DUTY CYCLE - DC - 35% @ 150A
- DUTY CYCLE - AC - 35% @ 105A

Product Brochure For W171A

Specific Features



Tig Torch



Amperage Control Dial and On Off Button

Recommended Accessories

W10361

Magnetic TIG Torch Rest



W1142

Ø1.6mm TIG Filler Rod - Mild Steel



W1142U

1.6mm Tig Tungsten Electrode - Thoriated Red



W1142V

2.4m Tig Tungsten Electrode - Thoriated Red



W1142W

3.2mm Tig Tungsten Electrode - Thoriated Red



W1142X

1.6mm Tig Tungsten Electrode - Zirconiated White



W1142Y

2.4mm Tig Tungsten Electrode - Zirconiated White



W1142Z

3.2mm Tig Tungsten Electrode - Zirconiated White

