

Product Brochure For W992

PAPR WELDING HELMETS - U11152

Please Call



ORDER CODE:	~
MODEL:	~
Viewing Area (mm):	100x83.4mm
Cartridge Size (mm):	114x133x9.5mm
Arc Sensors (No.):	4
Light State:	4
Shade:	5-9 / 9-13
Shade Control:	Yes
Power On/off:	~
Sensitivity Control:	Adjustable (1-5 for low-high)
UV/IR Protection:	DIN15
Helmet Power Supply:	~
Respirator Power Supply:	Solar Cells & CR2450 Replaceable Battery
Switching Time Light To Dark:	0.08ms
Delay Time Dark To Light (Seconds) (sec):	0.1-0.9s
TIG Rated Minimum (amp):	3A
Grinding Function (Yes / No):	Yes
Inactive Shade (Grind/Off):	~
Operating Temperature:	-10°C to 65°C
Storing Temperature:	-20°C to 85°C
Helmet Material:	~
Application Range:	~
Standard:	CE EN379, ANSI Z87.1, CSA Z94.3, & AS/NZS 1337.1 B (High Impact) & AS/NZS 1338.1 (Auto-Darkening) & AS/NZS 1716:2012
Total Weight (grams):	~



Description

The PAPR Welding Helmet TH3 lets you keep your lungs as protected as your eyes and face with the added respirator to keep fumes and gas out.

Features

- TH3 filter protection stops 99.8% of fine particles, weld fumes and gas
- With up to 8 hours of battery life, you can work all day on a single charge
- Top-of-the-line optical clarity with 1/1/1/1 classifications
- Outer Lens: PUMRBOP
- Inner Lens: PUMRWXIP
- Harness: UMRWXHR